

CUDY

Access Point Cudy BE11000 / Tri Band Wi Fi 7 / 2.5G – Bardhë

SKU: 25011222 · EAN: 6971690793586

SPECIFIKAT TEKNIKE	
65 specifikat e produktit	
ATRIBUTI	VLERA
Features	
2.4 GHz	Yes
5 GHz	Yes
6 GHz	Yes
Maximum data transfer rate	5760 Mbit/s
Maximum data transfer rate (2.4 GHz)	688 Mbit/s
Maximum data transfer rate (5 GHz)	4320 Mbit/s
Maximum data transfer rate (6 GHz)	5760 Mbit/s
Ethernet LAN data rates	2500 Mbit/s
Networking standards	IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11be, IEEE 802.11g, IEEE 802.11n, IEEE 802.11b
MIMO	Yes
MIMO type	Multi User MIMO
VLAN support	Yes
Virtual LAN features	Tagged VLAN
BeamForming	Yes
Maximum outdoor range	260 m
Security	
Security algorithms	WPA, WPA2, WPA3
MAC address filtering	Yes
IGMP snooping	Yes
Protocols	
DHCP client	Yes
Management features	
Syslog	Yes
Cloud-managed	Yes
Ports & interfaces	

Interface	2
Ethernet LAN (RJ-45) ports	1
SFP/SFP+ slots quantity	1
WAN connection	SFP+, Ethernet (RJ-45)
DC-in jack	Yes
Power	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	Passive PoE
DC voltage range	48-57 V
Output voltage	12 V
Output current	2 A
Power consumption (typical)	12 W
Power consumption (max)	20 W
Design	
Placement	Ceiling, Wall
Product colour	White
Reset button	Yes
LED indicators	System
Antenna	
Antenna type	Internal
Antennas quantity	6
Antenna gain level (max)	5.8 dBi
Performance	
Processor frequency	1500 MHz
Flash memory	128 MB
Internal memory	512 MB
Technical details	
Products per shipping (inner) case	10 pc(s)
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC)
Weight & dimensions	
Width	231.9 mm
Depth	57.1 mm
Height	231.9 mm
Weight	578.2 g

Packaging data	
Package width	310 mm
Package depth	238 mm
Package height	73 mm
Package weight	944 g
Packaging content	
AC adapter included	No
PoE adapter included	No
Cables included	LAN (RJ-45)
Mounting kit	Yes
Quick start guide	Yes
Bundled software	1
Operational conditions	
Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 95%
Logistics data	
Warranty period	1 year(s)
Country of origin	China