

DIGITUS

DIGITUS Industrial Fast Ethernet PoE Switch 4 Port + 1 Uplink | Unmanaged | DN-650107

SKU: 25011264 · EAN: 4016032458852

SPECIFIKAT TEKNIKE**36 specifikat e produktit**

ATRIBUTI	VLERA
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	5
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX
Cable types supported	Cat3, Cat4, Cat5
Full duplex	Yes
Flow control support	Yes
Auto MDI/MDI-X	Yes
MAC address auto-learning supported	Yes
MAC address auto-aging supported	Yes
Data transmission	
Switching capacity	1 Gbit/s
MAC address table	2000 entries
Store-and-forward	Yes
Design	
Product colour	Black, Blue
Housing material	Metal
LED indicators	Yes
Wall mountable	Yes
DIN rail mounting	Yes
Number of fans	0 fan(s)
Performance	
Mean time between failures (MTBF)	300000 h

Power	
Power supply included	No
Redundant power supply (RPS) support	Yes
DC input voltage	48 - 57 V
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	4
Power over Ethernet (PoE) power per port	30 W
Operational conditions	
Operating temperature (T-T)	-40 - 85 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%
Weight & dimensions	
Width	86 mm
Depth	128 mm
Height	34 mm
Packaging content	
User guide	Yes
Logistics data	
Harmonized System (HS) code	85176990