

CAMBIUM NETWORKS

Cambium cnMatrix EX1010-M 8+2 Port Managed Switch – Gigabit L2 Enterprise Switch 20Gbps Fanless

SKU: 25011275

SPECIFIKAT TEKNIKE

50 specifikat e produktit

ATRIBUTI	VLERA
Management features	
Switch type	Managed
Switch layer	L2/L3
Quality of Service (QoS) support	Yes
ARP inspection	Yes
Configuring Location Settings (CLI)	Yes
MIB support	Y
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
SFP+ module slots quantity	2
Network	
Networking standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ac, IEEE 802.3ad, IEEE 802.3u, IEEE 802.3x
10G support	No
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Auto MDI/MDI-X	Yes
Spanning tree protocol	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
VLAN support	Yes
Number of VLANs	4000
Data transmission	
Throughput	20 Gbit/s
MAC address table	16000 entries

Static route	Yes
Jumbo frames support	Yes
Jumbo frames	9000
Security	
DHCP features	DHCP snooping
Access Control List (ACL)	Yes
IGMP snooping	Yes
Security algorithms	SSH, SSH-2
SSH/SSL support	Yes
Multicast features	
Multicast support	Yes
Protocols	
Management protocols	SNMP v1/v2/v3
Design	
Rack mounting	Yes
Form factor	1U
Product colour	Grey
LED indicators	Yes
Performance	
Built-in processor	Yes
Processor frequency	800 MHz
Internal memory	512 MB
Flash memory	128 MB
Power	
Power source	AC
AC input voltage	100 - 240 V
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	55 - 95%
Weight & dimensions	
Width	210 mm
Depth	88 mm

Height	250 mm
Weight	1.6 kg