

EPSON

# Printer Termal Epson TM-T20III (011) POS Receipt Printer / USB + RS-232 / 203 dpi / 250 mm/s – Zezë

SKU: 19007782 · EAN: 8715946669649

## SPECIFIKAT TEKNIKE

### 72 specifikat e produktit

| ATRIBUTI                          | VLERA                  |
|-----------------------------------|------------------------|
| <b>Printing</b>                   |                        |
| Maximum resolution                | 203 x 203 DPI          |
| Print speed                       | 250 mm/sec             |
| Character density                 | 22.6 cpi               |
| Printing characters               | Text, Graphic, Barcode |
| Character sets                    | ANK                    |
| Print technology                  | Direct thermal         |
| Type                              | POS printer            |
| <b>Paper handling</b>             |                        |
| Maximum roll diameter             | 8.3 cm                 |
| Supported paper width             | 80 mm                  |
| <b>Ports &amp; interfaces</b>     |                        |
| USB port                          | Yes                    |
| USB 2.0 ports quantity            | 1                      |
| USB connector                     | USB Type-B             |
| Serial interface                  | Yes                    |
| Serial interface type             | RS-232                 |
| Connectivity technology           | Wired                  |
| Serial ports quantity             | 1                      |
| Standard interfaces               | RS-232, USB 2.0        |
| <b>Network</b>                    |                        |
| Ethernet LAN                      | No                     |
| Wi-Fi                             | No                     |
| <b>Features</b>                   |                        |
| Sound pressure level (printing)   | 55 dB                  |
| Mean time between failures (MTBF) | 360000 h               |
| Cutter                            | Yes                    |

|                                   |                                                                       |
|-----------------------------------|-----------------------------------------------------------------------|
| Half-cutter                       | Yes                                                                   |
| Autocutter durability             | 1.5 million cuts                                                      |
| Paper save function               | Yes                                                                   |
| Print head life                   | 150 km                                                                |
| Country of origin                 | Philippines                                                           |
| Mounting position                 | Horizontal/Vertical                                                   |
| Wall mountable                    | Yes                                                                   |
| Built-in sensors details          | Roll paper cover open sensor, Paper End Sensor, Paper Near End Sensor |
| Safety                            | UL, CSA, TÜV                                                          |
| Certification                     | FCC-Class A, CE, EN55022-Class A                                      |
| <b>Design</b>                     |                                                                       |
| Product colour                    | Black                                                                 |
| <b>Power</b>                      |                                                                       |
| Power source type                 | AC                                                                    |
| AC input voltage                  | 24 V                                                                  |
| Power consumption                 | 1800 mA                                                               |
| Power consumption (standby)       | 100 mA                                                                |
| <b>Operational conditions</b>     |                                                                       |
| Operating temperature (T-T)       | 5 - 45 °C                                                             |
| Storage temperature (T-T)         | -10 - 50 °C                                                           |
| Operating relative humidity (H-H) | 10 - 90%                                                              |
| Storage relative humidity (H-H)   | 10 - 90%                                                              |
| <b>Weight &amp; dimensions</b>    |                                                                       |
| Width                             | 140 mm                                                                |
| Depth                             | 199 mm                                                                |
| Height                            | 146 mm                                                                |
| Weight                            | 1.7 kg                                                                |
| <b>Packaging data</b>             |                                                                       |
| Cables included                   | AC                                                                    |
| Quantity per pack                 | 1 pc(s)                                                               |
| Package width                     | 192 mm                                                                |
| Package depth                     | 235 mm                                                                |
| Package height                    | 280 mm                                                                |
| Package weight                    | 2.62 kg                                                               |
| <b>Packaging content</b>          |                                                                       |

|                                     |                        |
|-------------------------------------|------------------------|
| Drivers included                    | Yes                    |
| Quick start guide                   | Yes                    |
| AC adapter included                 | Yes                    |
| <b>Print technology</b>             |                        |
| Column capacity                     | 48/64                  |
| <b>Logistics data</b>               |                        |
| Pallet weight (UK)                  | 0 g                    |
| Harmonized System (HS) code         | 84433210               |
| Products per master (outer) case    | 4 pc(s)                |
| Master (outer) case width           | 400 mm                 |
| Master (outer) case length          | 490 mm                 |
| Master (outer) case height          | 295 mm                 |
| Master (outer) case gross weight    | 0 g                    |
| Products per pallet                 | 112 pc(s)              |
| Products per pallet layer           | 16 pc(s)               |
| Pallet gross weight                 | 0 g                    |
| Products per pallet (UK)            | 168 pc(s)              |
| Products per pallet layer (UK)      | 24 pc(s)               |
| <b>Technical details</b>            |                        |
| Lifetime                            | 15000000 lines         |
| <b>Other features</b>               |                        |
| Buffer size                         | 4 KB                   |
| Mean cycles between failures (MCBF) | 60000000               |
| Print head life                     | 150.000.000 Impulse    |
| Print head life                     | 150 million characters |