

Iiyama

Monitor iiyama Prolite XUB2595WSU-B5 25" (1920x1200) LED IPS 16:10 4ms VGA HDMI DP USB LS Pivot Black

SKU: 16007232 · EAN: 4948570121465

SPECIFIKAT TEKNIKE	
86 specifikat e produktit	
ATRIBUTI	VLERA
Display	
Display diagonal	63.5 cm (25")
Display resolution	1920 x 1200 pixels
HD type	WUXGA
Native aspect ratio	16:10
Display technology	LED
Panel type	IPS
Display brightness (typical)	300 cd/m²
Response time	4 ms
Response time measurement type	GTG (Gray to Gray)
Display surface	Matt
Screen shape	Flat
Contrast ratio (typical)	1000:1
Contrast ratio (dynamic)	5000000:1
Viewing angle. horizontal	178°
Viewing angle. vertical	178°
Display number of colours	16.7 million colours
Horizontal scan range	30 - 89 kHz
Viewable size. horizontal	53.5 cm
Viewable size. vertical	33.9 cm
Display diagonal (metric)	63.36 cm
DDC/CI	Yes
Performance	
AMD FreeSync	Yes
Flicker-free technology	Yes
Low Blue Light technology	Yes

Multimedia	
Number of speakers	2
RMS rated power	4 W
Built-in speaker(s)	Yes
Built-in camera	No
Design	
Market positioning	Office
Product colour	Black
Ports & interfaces	
Built-in USB hub	Yes
USB hub version	2.0
Number of downstream ports	2
VGA (D-Sub) ports quantity	1
HDMI	Yes
HDMI ports quantity	1
DisplayPorts quantity	1
Headphone out	Yes
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
Cable management	Yes
Cable lock slot	Yes
Cable lock slot type	Kensington
Height adjustment	Yes
Adjustable height (max)	15 cm
Pivot	Yes
Pivot angle	-90 - 90°
Swivelling	Yes
Swivel angle range	-45 - 45°
Tilt adjustment	Yes
Tilt angle range	23 - 5°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	German, English, French, Japanese, Dutch, Polish, Russian

Power	
Energy efficiency class (SDR)	F
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	21 kWh
Power consumption (typical)	28 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Weight & dimensions	
Width (with stand)	546.5 mm
Depth (with stand)	209.5 mm
Height (with stand)	526.5 mm
Weight (with stand)	5 kg
Height (without stand)	376.5 mm
Packaging data	
Package width	629 mm
Package depth	160 mm
Package height	452 mm
Package weight	6.5 kg
Package type	Box
Packaging content	
Cables included	AC, USB, HDMI, DisplayPort
Quick start guide	Yes
Sustainability	
Sustainability certificates	ErP, TCO
Other features	
Second display effective viewing area	535.4 x 338.7 mm
User controls	luminance (contrast, brightness, i-Style colour, ACR, ECO), image settings (pixel clock, phase, H. position, V. position, aspect ratio), colour settings (gamma, 6-Axis, colour temp.), OSD (H. position, V. position, OSD time, language), extra (reset, DDC/CI, signal select, OD, audio source, opening logo, FreeSync, information)
Packaging content	quick start guide, safety guide
Weight	5 kg

Width	546.5 mm
Depth	209.5 mm
Control panel	Auto/Signal Select, -/ECO, +/-Volume, Menu, Power
Compliance certificates	CE, EAC, PSE, REACH, RoHS, TÜV mark, UKCA, VCCI, WEEE