

VIEWSONIC TECHNOLOGY

Monitor Viewsonic VG2709-2K-MH DU-2 / 27"/ Quad HD IPS / LED / 100Hz / 4ms / HDMI+DisplayPort+USB - Zezë

SKU: 16007248 · EAN: 0766907028584

SPECIFIKAT TEKNIKE

96 specifikat e produktit

ATRIBUTI	VLERA
Display	
Display diagonal	68.6 cm (27")
Display resolution	2560 x 1440 pixels
HD type	Quad HD
Native aspect ratio	16:9
Display technology	LED
Panel type	IPS
LED backlight	Yes
Touchscreen	No
Display brightness (typical)	350 cd/m ²
Response time	4 ms
Anti-glare screen	Yes
Screen shape	Flat
Supported graphics resolutions	2560 x 1440
Supported video modes	1440p
Contrast ratio (typical)	1000:1
Contrast ratio (dynamic)	50000000:1
Maximum refresh rate	100 Hz
Viewing angle. horizontal	178°
Viewing angle. vertical	178°
Display number of colours	16.7 million colours
Display diagonal (metric)	69 cm
High Dynamic Range (HDR) supported	Yes
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)
Colour depth	8 bit
sRGB coverage (typical)	104%
NTSC coverage (typical)	72%

Performance	
Flicker-free technology	Yes
Low Blue Light technology	Yes
Multimedia	
Number of speakers	2
RMS rated power	5 W
Built-in speaker(s)	Yes
Built-in camera	No
Design	
Market positioning	Office
Product colour	Black
Ports & interfaces	
Built-in USB hub	Yes
USB upstream port type	USB Type-A, USB Type-C
Number of upstream ports	2
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	2
USB Type-C DisplayPort Alternate Mode	Yes
HDMI	Yes
HDMI ports quantity	1
HDMI version	1.4/2.0/2.2
DisplayPorts quantity	1
Headphone out	Yes
Headphone outputs	1
Headphone connectivity	3.5 mm
Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
Cable management	Yes
Cable lock slot	Yes
Cable lock slot type	Kensington
Height adjustment	Yes
Adjustable height (max)	13 cm
Pivot	Yes

Pivot angle	-90 - 90°
Swivelling	Yes
Swivel angle range	0 - 360°
Tilt adjustment	Yes
Tilt angle range	-3.5 - 28°
Plug and Play	Yes
LED indicators	Yes
Power	
Energy efficiency class (SDR)	F
Energy efficiency class (HDR)	F
Energy consumption (SDR) per 1000 hours	22 kWh
Energy consumption (HDR) per 1000 hours	26 kWh
Power consumption (typical)	22.3 W
Power consumption (standby)	0.5 W
Power consumption (max)	36 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 90%
Weight & dimensions	
Width (with stand)	613.8 mm
Depth (with stand)	233.3 mm
Height (with stand)	538 mm
Weight (with stand)	6.7 kg
Width (without stand)	613.8 mm
Depth (without stand)	51 mm
Height (without stand)	365.8 mm
Weight (without stand)	4.4 kg
Packaging data	
Package width	775 mm
Package depth	140 mm
Package height	465 mm
Package weight	8.1 kg

Packaging content	
Stand included	Yes
Cables included	AC
Manual	Yes
Other features	
Weight	6.7 kg
Logistics data	
Pallet gross width	120 cm
Pallet gross length	100 cm
Pallet gross height	2.13 m
Products per master (outer) case	1 pc(s)
Harmonized System (HS) code	8528521000