

THERMALTAKE

Furnizues Energjie (PSU) 850W Thermaltake Toughpower PF3

SKU: 17008747 · EAN: 4713227536561

SPECIFIKAT TEKNIKE

48 specifikat e produktit

ATRIBUTI	VLERA
Power	
Total power	850 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Input current	10 A
Power Factor Correction (PFC) type	Active
Combined power (+3.3V)	100 W
Combined power (-12V)	849.6 W
Combined power (+5V)	100 W
Combined power (-12V)	3.6 W
Combined power (+5Vsb)	12.5 W
Max output current (+3.3V)	20 A
Max output current (-12V)	70.8 A
Max output current (+5V)	20 A
Max output current (-12V)	0.3 A
Max output current (+5Vsb)	2.5 A
Efficiency	70%
Ports & interfaces	
Motherboard power connector	24-pin ATX
Motherboard power cable length	60 cm
Number of SATA power connectors	8
SATA power cable length	150,500 mm
Peripheral (Molex) power connectors (4-pin)	4
Peripheral (Molex) power cable length	150,500 mm
EPS power connector (4+4 pin)	Yes
PCI Express power connectors (6+2 pin)	4
PCI Express power connectors (16-pin)	1

ATX Power connector (24-pin)	Yes
Cabling type	Fully-Modular
Performance	
80 PLUS certification	80 PLUS Platinum
Purpose	PC
Power supply unit (PSU) form factor	ATX
ATX version	3.0
Silent mode	Yes
Bearing technology	FDB
Mean time between failures (MTBF)	100000 h
Design	
Product colour	Black
Cooling type	Active
Fan diameter	12 cm
Number of fans	1 fan(s)
On/off switch	Yes
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 85%
Storage relative humidity (H-H)	5 - 95%
Packaging content	
Cables included	PCIe, Peripheral (Molex), SATA
Safety regulation & standards	
Safety	CE/FCC/UKCA/ICES/LVD/TUV/cTUVus/CB/CCC/BSMI
Weight & dimensions	
Width	140 mm
Depth	150 mm
Height	86 mm