

DELL

Monitor DELL Pro P2426 / 24.1"/ WUXGA IPS / LCD / 100Hz / 8ms / HDMI+DP+USB - Zezë

SKU: 16007267 · EAN: 5397321029526

SPECIFIKAT TEKNIKE

106 specifikat e produktit

ATRIBUTI	VLERA
Display	
Display diagonal	61.2 cm (24.1")
Display resolution	1920 x 1200 pixels
HD type	WUXGA
Native aspect ratio	16:10
Display technology	LCD
Panel type	IPS
LED backlight	Yes
Backlight type	Edge LED
Touchscreen	No
Display brightness (peak)	300 cd/m ²
Response time	8 ms
Response time measurement type	GTG (Gray to Gray)
Anti-glare screen	Yes
Screen shape	Flat
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1600 x 900, 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA)
Supported video modes	1080p, 720p, 576p, 480p
Contrast ratio (typical)	1500:1
Maximum refresh rate	100 Hz
Viewing angle. horizontal	178°
Viewing angle. vertical	178°
Display number of colours	16.7 million colours
Response time (fast)	5 ms
Pixel pitch	0.27 x 0.27 mm
Pixel density	94 ppi
Viewable size. horizontal	61.1 cm

Viewable size. vertical	51.8 cm
Viewable size diagonal	32.4 cm
Digital horizontal frequency	30 - 127 kHz
Digital vertical frequency	48 - 100 Hz
Surface hardness	3H
sRGB coverage (typical)	99%
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Flicker-free technology	Yes
Low Blue Light technology	Yes
Multimedia	
Built-in speaker(s)	No
Built-in camera	No
Design	
Market positioning	Consumer
Product colour	Grey
Ports & interfaces	
Built-in USB hub	Yes
USB upstream port type	USB Type-B
Number of USB Type-B upstream ports quantity	1
USB Type-A downstream ports quantity	3
USB Type-C downstream ports quantity	1
HDMI	Yes
HDMI ports quantity	1
HDMI version	1.4
DisplayPorts quantity	1
DisplayPort out version	1.4
Headphone out	No
HDCP	Yes
HDCP version	1.4
Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Cable management	Yes

Cable lock slot	Yes
Cable lock slot type	Kensington
Height adjustment	Yes
Adjustable height (max)	15 cm
Pivot	Yes
Pivot angle	-90 - 90°
Swivelling	Yes
Swivel angle range	-45 - 45°
Tilt adjustment	Yes
Tilt angle range	-5 - 21°
Power	
Energy efficiency class (SDR)	D
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	14 kWh
Power consumption (typical)	13.6 W
Power consumption (standby)	0.3 W
Power consumption (max)	68 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Input current	1.5 A
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	5 - 90%
Non-operating altitude	5000 - 12192 m
Weight & dimensions	
Width (with stand)	531.8 mm
Depth (with stand)	181.8 mm
Height (with stand)	511.2 mm
Weight (with stand)	4.57 kg
Width (without stand)	531.8 mm
Depth (without stand)	50 mm

Height (without stand)	343.7 mm
Weight (without stand)	3.07 kg
Bezel width (side)	6.7 mm
Bezel width (top)	6.7 mm
Bezel width (bottom)	1.3 cm
Packaging data	
Package weight	6.74 kg
Packaging content	
Stand included	Yes
Cables included	Power, DisplayPort, USB Type-A to USB Type-B
DisplayPort cable length	1.8 m
Sustainability	
Sustainability certificates	ENERGY STAR, TCO
Doesn't contain	PVC/BFR, Arsenic, Mercury
Carbon footprint	
Total carbon footprint (kg of CO2e)	152
Carbon emissions, manufacturing (kg of CO2e)	70.68
Carbon emissions, logistics (kg of CO2e)	13.53
Carbon emissions, energy usage (kg of CO2e)	62.17
Carbon emissions, end-of-life (kg of CO2e)	5.62
PAIA version	GaBi version 2, 2026
Other features	
Compliance certificates	RoHS