

CUDY

Ruter Cudy AC1200 Wi-Fi 4G LTE-Cat6 Gigabit - Bardhë

SKU: 25011409 · EAN: 6971690792879

SPECIFIKAT TEKNIKE	
76 specifikat e produktit	
ATRIBUTI	VLERA
WAN connection	
Ethernet WAN	Yes
DSL WAN	Yes
SIM card slot	Yes
WAN connection type	RJ-45
Wireless LAN features	
Wi-Fi band	Dual-band (2.4 GHz / 5 GHz)
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)
WLAN data transfer rate (max)	867 Mbit/s
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
WLAN data transfer rate (first band)	300 Mbit/s
WLAN data transfer rate (second band)	867 Mbit/s
Network	
Ethernet LAN	Yes
Ethernet LAN interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Cabling technology	10/100/1000Base-T(X)
Port forwarding	Yes
Port triggering	Yes
Dynamic DNS (DDNS)	Yes
VPN server	Yes
Mobile network	
Mobile network generation	4G
Dual SIM support	No
2G standards	Edge, GSM
3G standards	WCDMA
4G standard	LTE-TDD & LTE-FDD
SIM card type	NanoSIM

Short Message Service (SMS)	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	4
USB port	No
DC-in jack	Yes
Management features	
Wi-Fi Multimedia (WMM)/(WME)	Yes
Wake-on-LAN ready	Yes
Reset button	Yes
WPS push button	Yes
MU-MIMO technology	Yes
MIMO	Yes
Security	
Security algorithms	WPA, WPA2, WPA3
Guest access	Yes
DoS attack prevention	Yes
MAC address filtering	Yes
IGMP snooping	Yes
DMZ support	Yes
Protocols	
DHCP client	Yes
DHCP server	Yes
Universal Plug and Play (UPnP)	Yes
Supported network protocols	IPv4 / IPv6
Design	
Product colour	White
Wall mountable	Yes
LED indicators	System, WLAN
Product type	Desktop/pole router
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC)
Packaging content	
Cables included	LAN (RJ-45)
Mounting kit	Yes
Quick installation guide	Yes

Antenna	
Antenna design	Internal & external
Antenna connector type	SMA
Antenna gain level (max)	5 dBi
Antennas quantity	4
Detachable antenna(s)	Yes
Features	
Internal memory	128 MB
Flash memory	16 MB
Power	
Power source type	PoE
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Output voltage	12 V
Output current	1 A
Power consumption (typical)	3.6 W
Operational conditions	
Storage temperature (T-T)	-40 - 70 °C
System requirements	
Linux operating systems supported	Yes
Mac operating systems supported	Yes
Weight & dimensions	
Width	190 mm
Depth	50 mm
Height	148.8 mm
Weight	300 g
Packaging data	
Package width	270 mm
Package depth	58 mm
Package height	168 mm
Package weight	595 g