

INFOCUS

Projektor InFocus Authentic I IN1048SL / Business DLP / 6000 ISO Lumen / Full HD / HDMI+VGA+USB – Bardhë

SKU: 18000609 · EAN: 0850053009648

SPECIFIKAT TEKNIKE

77 specifikat e produktit

ATRIBUTI	VLERA
Projector	
Smart projector	No
Projection distance	1 - 9.3 m
Projector brightness	6000 ANSI lumens
Projection technology	DLP
Projector native resolution	1080p (1920x1080)
Contrast ratio (typical)	2000000:1
Native aspect ratio	16:9
Uniformity	85%
Horizontal scan range	15.4 - 91.1 kHz
Vertical scan range	24 - 120 Hz
Keystone correction. horizontal	30°
Keystone correction. vertical	30°
Matrix size	1.65 cm (0.65")
Matrix type	DMD
Light source	
Light source type	Laser
Service life of light source	30000 h
Lens system	
Focus	Manual
Focal length range	20.91 - 32.62 mm
Zoom capability	Yes
Zoom type	Manual
Zoom ratio	1.6:1
Throw ratio	1.4 ~ 2.24
Vertical lens shift range	103 - 118%
Offset	113%

Video	
Full HD	Yes
3D	Yes
Ports & interfaces	
HDMI connector type	Full-size
HDMI version	1.4/2.0
S-Video inputs quantity	1
HDBaseT port	Yes
Service port type	USB Type-A
USB 2.0 ports quantity	1
USB 2.0 Type-A ports quantity	1
Headphone outputs	1
Microphone in	Yes
Serial interface type	RS-232
VGA (D-Sub) ports quantity	3
HDMI ports quantity	2
Composite video in	1
DVI port	No
AC (power) in	Yes
Network	
Smart TV	No
Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	1
Wi-Fi	No
Storage	
Card reader integrated	No
Features	
Interactive	No
Noise level (economic mode)	28 dB
Noise level	30 dB
Multimedia	
Built-in speaker(s)	Yes
RMS rated power	10 W
Number of built-in speakers	1
Design	

Market positioning	Presentation
Product type	Standard throw projector
Product colour	White
Placement	Ceiling, Desktop, Floor, Wall
Cable lock slot	Yes
Cable lock slot type	Kensington
Display	
Built-in display	No
Power	
Power source	AC
Power consumption (typical)	190 W
Power consumption (standby)	0.5 W
Power consumption (max)	341 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Operational conditions	
Operating temperature (T-T)	5 - 40 °C
Storage temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 85%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3048 m
Weight & dimensions	
Width	374 mm
Depth	302 mm
Height	117 mm
Weight	5.5 kg
Packaging content	
Remote control included	Yes
Cables included	AC, VGA
Manual	Yes