

AOC

Monitor AOC 24P4U / 23.8" / Full HD IPS / 120 Hz / 4ms / USB +USB-C + VGA + HDMI + DP - Zezë

SKU: 16007374 · EAN: 4038986142878

SPECIFIKAT TEKNIKE

110 specifikat e produktit

ATRIBUTI	VLERA
Display	
Display diagonal	60.5 cm (23.8")
Display resolution	1920 x 1080 pixels
HD type	Full HD
Native aspect ratio	16:9
Panel type	IPS
LED backlight	Yes
Backlight type	W-LED
Touchscreen	No
Display brightness (typical)	300 cd/m ²
Response time	4 ms
Response time measurement type	GTG (Gray to Gray)
Anti-glare screen	Yes
Screen shape	Flat
Contrast ratio (typical)	1500:1
Contrast ratio (dynamic)	20000000:1
Maximum refresh rate	120 Hz
Viewing angle. horizontal	178°
Viewing angle. vertical	178°
Display number of colours	16.7 million colours
Pixel pitch	0.2745 x 0.2745 mm
Pixel density	93 ppi
Horizontal scan range	30 - 85 kHz
Vertical scan range	48 - 75 Hz
Digital horizontal frequency	30 - 140 kHz
Digital vertical frequency	48 - 120 Hz
Display diagonal (metric)	60.4 cm

High Dynamic Range (HDR) supported	Yes
Surface hardness	3H
sRGB coverage (typical)	111.1%
Colour gamut standard	sRGB
Performance	
AMD FreeSync refresh rate range	48 - 120 Hz
Flicker-free technology	Yes
Low Blue Light technology	Yes
Multimedia	
Number of speakers	2
RMS rated power	4 W
Built-in speaker(s)	Yes
Built-in camera	No
Design	
Market positioning	Home
Product colour	Black
Front bezel colour	Black
Ports & interfaces	
Built-in USB hub	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB Type-A downstream ports quantity	3
USB Type-C downstream ports quantity	1
VGA (D-Sub) ports quantity	1
HDMI	Yes
HDMI ports quantity	1
HDMI version	1.4
DisplayPorts quantity	1
DisplayPort version	1.2
Audio input	Yes
Audio output	Yes
Headphone out	Yes
HDCP	Yes
HDCP version	1.4
Ergonomics	
VESA mounting	Yes

Panel mounting interface	100 x 100 mm
Cable lock slot	Yes
Cable lock slot type	Kensington
Height adjustment	Yes
Adjustable height (max)	15 cm
Pivot	Yes
Pivot angle	-90 - 90°
Swivelling	Yes
Swivel angle range	-175 - 175°
Tilt adjustment	Yes
Tilt angle range	-5 - 30°
Power	
Energy efficiency class (SDR)	C
Energy efficiency class (HDR)	D
Energy consumption (SDR) per 1000 hours	11 kWh
Energy consumption (HDR) per 1000 hours	13 kWh
Power consumption (typical)	12.09 W
Power consumption (standby)	0.3 W
Power consumption (max)	73 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Input current	1.5 A
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-25 - 55 °C
Operating relative humidity (H-H)	10 - 85%
Storage relative humidity (H-H)	5 - 93%
Operating altitude	0 - 5000 m
Non-operating altitude	0 - 12192 m
Weight & dimensions	
Width (with stand)	542.4 mm
Depth (with stand)	232.9 mm
Height (with stand)	507.4 mm

Weight (with stand)	4.72 kg
Width (without stand)	542.4 mm
Depth (without stand)	51 mm
Height (without stand)	320.2 mm
Weight (without stand)	2.98 kg
Packaging data	
Package width	650 mm
Package depth	139 mm
Package height	455 mm
Package weight	6.48 kg
Packaging content	
Stand included	Yes
Cables included	AC, HDMI, DisplayPort
DisplayPort cable length	1.8 m
HDMI cable length	1.8 m
Power cable length	1.8 m
Sustainability	
Sustainability certificates	EPEAT Gold, TCO
Doesn't contain	Mercury, PVC/BFR
Other features	
Local dimming	Yes
Warranty period	5 year(s)
Compliance certificates	CE
Mean time between failures (MTBF)	70000 h
Certification	WEEE, REACH compliant, RoHS compliant, CB, TUV-GS-Mark, TUV Ergo, EAC, FCC