

AXIS

Kamerë Sigurie IP CCTV Axis P3747-PLVE, 4 × 5MP, 3.18–7.42 mm, 2.3x, 360°, IR, PoE, IP66, IK10 - Zezë/Bardhë

SKU: 26025664 · EAN: 7331021086135

SPECIFIKAT TEKNIKE	
110 specifikat e produktit	
ATRIBUTI	VLERA
Performance	
Type	IP security camera
Placement supported	Outdoor
Connectivity technology	Wired
Feature	PTZ control
Feature	Preset points
Maximum operating distance	20 m
Feature	Wide Dynamic Range (WDR)
Feature	Day/night mode
Feature	Infrared (IR) cut-off filter
Feature	Remote viewing
Feature	Built-in light
Number of languages	19
Design	
Form factor	Dome
Mounting type	Ceiling/wall
Product colour	Black, White
LED indicators	Activity
Housing material	Aluminium, Polycarbonate (PC)
International Protection (IP) code	IP66
IK code	IK10
Camera	
Feature	Camera tilt control
Minimum illumination	0.1 lx
Horizontal field of view (thermal module)	360°
Lens viewing angle. horizontal	360°
Lens viewing angle. vertical	71.5 - 30.0°

Camera pixel size	2 µm
Camera shutter speed	1/19500 - 1 s
Image sensor	
Number of sensors	1
Optical sensor size	25.4 / 2.78 mm (1 / 2.78")
Feature	Progressive scan
Sensor type	CMOS
Panoramic camera	
Sensor type (panoramic camera)	CMOS
Signal-to-Noise Ratio (SNR) (panoramic camera)	55 dB
Lens system	
Feature	Zoom capability
Number of lenses	3
Focal length range	3.18 - 7.42 mm
Feature	Fixed focus
Focus	Motorized
Night vision	
Feature	Night vision
Night vision distance	20 m
LED type	IR
Number of illumination LEDs	2
Infra-red wavelength	850 nm
Video	
Maximum resolution	2592 x 1944 pixels
Total megapixels	5 MP
Video formats supported	H.264, H.265
Video compression formats	M-JPEG, MPEG, MPEG4
Supported graphics resolutions	640 x 360, 640 x 480 (VGA), 2560 x 1440, 2592 x 1944
Feature	Video recording
Frame rate	20 fps
Feature	Video intelligence analytic
Feature	Video streaming
Noise reduction technology	2D noise reduction, 3D noise reduction
Image quality adjustment	Brightness, Contrast, Mirror, Saturation, Sharpness
Feature	Privacy masking

Feature	Text caption overlay
Feature	Image stabilizer
Bit rate control	Variable Bit Rate (VBR)
Audio	
Feature	Built-in speaker(s)
Audio system	2-way
Feature	Audio system full duplex
Audio input channels	2.0 channels
Audio output channels	2.0 channels
Audio formats supported	RTSP
Frequency range	50 - 60 Hz
Feature	Audio detection
Network	
Feature	Ethernet LAN
Ethernet interface type	Fast Ethernet
Networking standards	IEEE 802.1AE, IEEE 802.1x, IEEE 802.3af, IEEE 802.3at
Feature	Quality of Service (QoS) support
Streaming method	Multicast
Number of simultaneous live view channels	4 channels
Storage	
Compatible memory cards	MicroSD (TransFlash), MicroSDHC, MicroSDXC
Flash memory	8192 MB
RAM capacity	4096 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Security	
Feature	Password protection
Feature	Video motion detection
Feature	Active tampering alarm
Feature	IP address filtering
Security algorithms	256-bit AES-XTS, FIPS 140-2, HTTPS, SNMP
Feature	HTTPS encryption
Alert notification type	E-mail
Feature	Privacy protection
Intelligent Video Surveillance (IVS) system features	Human detection, Vehicle detection

Feature	Motion sensor
Feature	Pixel counter
Feature	Human and vehicle targets classification
Feature	Digest authentication
Feature	Network access storage (NAS)
Management features	
Feature	Remotely operated
Power	
Power source type	PoE
Power consumption (typical)	10.8 W
Power consumption (max)	23.7 W
Operational conditions	
Operating temperature (T-T)	-40 - 50 °C
Storage temperature (T-T)	-40 - 65 °C
Operating relative humidity (H-H)	10 - 100%
Storage relative humidity (H-H)	5 - 95%
Weight & dimensions	
Width	141 mm
Depth	220 mm
Height	75 mm
Weight	3 kg
Features	
Feature	License plate recognition
Sustainability	
Compliance certificates	BSMI, CE, Federal Communications Commission (FCC), ICES, KC, RCM, REACH, RoHS, Trade Agreements Act (TAA), UL, VCCI, cUL
Packaging content	
Number of cameras	1
Feature	Mounting kit
Feature	Mounting brackets included
Memory card included	Yes
Feature	Manual
Other features	
Doesn't contain	BFR, CFR, PVC
Warranty period	5 year(s)