

YEALINK

Ruter Yealink W70B Stacioni i Bazës

SKU: 25011601 · EAN: 6938818307254

SPECIFIKAT TEKNIKE	
60 specifikat e produktit	
ATRIBUTI	VLERA
Performance	
Number of handsets supported (max)	10
Maximum range	300 m
CAT-iq	2.0
Number of VoIP accounts	10
Management protocols	SNTP/NTP, UDP/TCP/TLS
Security algorithms	AES, HTTPS, SHA-256, SHA-384, SHA-512, TLS
DECT standards	CAT-iq2.0
Voice codecs	AGC, AJB, AMR-WB, CNG, G.722, G.726, G.729, G.729A, PLC, VAD, iLBC
Networking standards	IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3af
Hearing aid compatibility	Yes
Music on hold function	Yes
XML browser	Yes
Auto-provision	Yes
Call management	
Conference call	Yes
Number of parallel conferences	3
Phonebook capacity (per handset)	1000 entries
Number of simultaneous calls (max)	20
Anonymous call	Yes
Anonymous call rejection	Yes
Call waiting	Yes
Call forwarding	Yes
Caller ID	Yes
Remote phonebook	Yes
Call transfer	Yes
Call hold	Yes

Switching between calls	Yes
Mute function	Yes
Speed dialling	Yes
Integrated voicemail	Yes
Redialing	Yes
Message Waiting Indication (MWI) function	Yes
Phonebook search/import/export function	Yes
Call history	Yes
Reset function	Yes
Emergency call	Yes
Shared Call Appearance (SCA)	Yes
System log export	Yes
Antenna	
Frequency range (EU)	1880 - 1900 MHz
Frequency range (US)	1920 - 1930 MHz
Ports & interfaces	
Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rate supported (max)	100 Mbit/s
Design	
Product colour	Grey
Full duplex	Yes
Wall mountable	Yes
LED indicators	Yes
Certification	CE, FCC, REACH
Power	
Input voltage	100 - 240 V
Output voltage	5 V
Output current	0.6 A
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 95%
Weight & dimensions	
Dimensions (WxDxH)	130 x 100 x 25.1 mm
Weight	3.61 kg

Package width	174 mm
Package depth	180 mm
Package height	63 mm
Package weight	4.15 kg
Packaging content	
Quick start guide	Yes
Power adapter included	Yes