

DELL

Monitor Konferencash Dell P3426WEB / 34"/ Wide Quad HD IPS LCD / 100Hz / 8ms / Webcam / USB-C+HDMI+DP - Zezë

SKU: 16007544 · EAN: 5397184962954

SPECIFIKAT TEKNIKE	
92 specifikat e produktit	
ATRIBUTI	VLERA
Display	
Display diagonal	86.4 cm (34")
Display technology	LCD
Panel type	IPS
LED backlight	Yes
LED backlighting type	Edge-LED
Display resolution	3440 x 1440 pixels
Display brightness	350 cd/m²
HD type	Wide Quad HD
Touchscreen	No
Native aspect ratio	21:9
Native refresh rate	100 Hz
Response time	8 ms
Contrast ratio (typical)	1500:1
Viewing angle. horizontal	178°
Viewing angle. vertical	178°
Display number of colours	1.07 billion colours
sRGB coverage (typical)	99%
Pixel pitch	0.2325 x 0.2325 mm
Active display area (W x H)	799.8 x 334.8 mm
Anti-glare screen	Yes
Camera	
Built-in camera	Yes
Megapixel (approx.)	4 MP
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2

RMS rated power	10 W
Design	
Product colour	Black
Screen shape	Curved
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Bezel width (bottom)	1.71 cm
Bezel width (side)	8.66 mm
Bezel width (top)	8.7 mm
Mounting type	Desk
Height adjustment	Yes
Height adjustment	15 cm
Pivot	No
Swivelling	Yes
Swivel angle range	-30 - 30°
Tilt angle range	-5 - 21°
Ports & interfaces	
HDMI ports quantity	1
HDMI version	2.1
DVI port	No
DisplayPorts quantity	1
Number of USB Type-B upstream ports quantity	1
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	2
USB port	Yes
USB Type-C DisplayPort Alternate Mode	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	90 W
USB charging port	Yes
Computer system	
Computer system	No
Windows operating systems supported	Yes
Mac operating systems supported	Yes
Performance	
On Screen Display (OSD)	Yes
HDCP	Yes

HDCP version	1.4
Power	
Power consumption (typical)	27 W
Power consumption (max)	220 W
Power consumption (standby)	0.5 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Energy efficiency scale	A to G
Energy efficiency class (SDR)	F
Energy consumption (SDR) per 1000 hours	27 kWh
Power supply type	Internal
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Display width	815.6 mm
Display depth	85.9 mm
Display height	392.8 mm
Display weight	7.18 kg
Width (with stand)	815.6 mm
Depth (with stand)	229.4 mm
Height (with stand)	573.2 mm
Weight (with stand)	9.61 kg
Packaging data	
Package weight	14.8 kg
Packaging content	
Stand included	Yes
Cables included	DisplayPort, USB Type-A to USB Type-B, USB Type-C to USB Type-C
Sustainability	
Sustainability certificates	ENERGY STAR, TCO
Network	
Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	1

Wi-Fi	No
Technical details	
Compliance certificates	RoHS
Carbon footprint	
Total carbon footprint (kg of CO2e)	334
Carbon emissions, manufacturing (kg of CO2e)	121.58
Carbon emissions, logistics (kg of CO2e)	29.73
Carbon emissions, energy usage (kg of CO2e)	123.58
Carbon emissions, end-of-life (kg of CO2e)	59.45
PAIA version	GaBi version 2, 2026