

ZEBRA

# Skaner Zebra LS2208 1D SR Multi-IF Kit (USB) – Gri

SKU: 19008592 · EAN: 0033587458421

| SPECIFIKAT TEKNIKE                |                                                                                                                                                                                            |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 19 specifikat e produktit         |                                                                                                                                                                                            |
| ATRIBUTI                          | VLERA                                                                                                                                                                                      |
| <b>Scanning</b>                   |                                                                                                                                                                                            |
| Sensor type                       | Laser                                                                                                                                                                                      |
| Tilt reading angle                | -30 - 30°                                                                                                                                                                                  |
| Pitch reading angle               | -65 - 65°                                                                                                                                                                                  |
| Yaw reading angle                 | -60 - 60°                                                                                                                                                                                  |
| Decoding standards                | UPC/EANUPC/EAN + SupplementalsUCC/EAN 128Code 39Code 39 Full ASCIICode 39 TriOpticCode 128Code 128 Full ASCIICodabarInterleaved 2/5Discrete 2/5Code 93MSICode 11IATAGS1 DataBarChinese 2/5 |
| Scan speed                        | 100 sec/page                                                                                                                                                                               |
| <b>Ports &amp; interfaces</b>     |                                                                                                                                                                                            |
| Standard interfaces               | USB                                                                                                                                                                                        |
| <b>Performance</b>                |                                                                                                                                                                                            |
| Product colour                    | White                                                                                                                                                                                      |
| <b>Power</b>                      |                                                                                                                                                                                            |
| Input voltage                     | 5 V                                                                                                                                                                                        |
| Power consumption                 | 130 mA                                                                                                                                                                                     |
| <b>Weight &amp; dimensions</b>    |                                                                                                                                                                                            |
| Weight                            | 146 g                                                                                                                                                                                      |
| <b>Operational conditions</b>     |                                                                                                                                                                                            |
| Operating temperature (T-T)       | 0 - 50 °C                                                                                                                                                                                  |
| Storage temperature (T-T)         | -40 - 70 °C                                                                                                                                                                                |
| Operating relative humidity (H-H) | 5 - 95%                                                                                                                                                                                    |
| <b>Logistics data</b>             |                                                                                                                                                                                            |
| Harmonized System (HS) code       | 84716070                                                                                                                                                                                   |
| <b>Other features</b>             |                                                                                                                                                                                            |
| Dimensions (WxDxH)                | 63 x 84 x 152 mm                                                                                                                                                                           |
| Safety                            | UL 60950-1, C22.2 No. 60950-1, EN 60950-1, IEC 60950-1                                                                                                                                     |
| Electromagnetic emissions         | FCC Part 15 Class B, ICES 003 Class B                                                                                                                                                      |

