

TP-LINK

Access Point TP-LINK EAP115 – 2.4 GHz / 300 Mbps – Bardhë

SKU: 25011740 · EAN: 6935364096939

SPECIFIKAT TEKNIKE	
66 specifikat e produktit	
ATRIBUTI	VLERA
Features	
2.4 GHz	Yes
5 GHz	No
6 GHz	No
Maximum data transfer rate	300 Mbit/s
Maximum data transfer rate (2.4 GHz)	300 Mbit/s
Ethernet LAN data rates	10,100,1000 Mbit/s
Frequency band	2.4 - 2.4835 GHz
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Cabling technology	10/100Base-T(X)
Automatic channel selection	Yes
Wi-Fi Multimedia (WMM)/(WME)	Yes
VLAN support	Yes
Virtual LAN features	VLAN mapping
Rate limiting	Yes
Wireless isolation	Yes
Quality of Service (QoS) support	Yes
Transmitting power (CE)	19 dBm
Transmitting power (FCC)	21 dBm
Receiver sensitivity	300M: -71dBm@10% PER150M: -75dBm@10% PER54M: -78dBm@10% PER11M: -93dBm@8% PER6M: -92dBm@10% PER1M: -96dBm@8% PER
Security	
Security algorithms	64-bit WEP, 128-bit WEP, 152-bit WEP, HTTPS, SNMP, SSH, WPA, WPA-PSK, WPA2-Enterprise, WPA2-PSK
MAC address filtering	Yes
Service Set Identifier (SSID) features	Multiple SSIDs
Number of SSID supported	8

System status alarm	Yes
Access Control List (ACL)	Yes
Management features	
Web-based management	Yes
Syslog	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
WAN connection	Ethernet (RJ-45), Wi-Fi
Power	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	Passive PoE
Output voltage	12 V
Output current	1 A
Power consumption (typical)	5 W
Design	
Placement	Ceiling, Wall
Product colour	White
Cable lock slot	Yes
Cable lock slot type	Kensington
On/off switch	Yes
Reset button	Yes
LED indicators	Yes
Antenna	
Antenna type	Internal
Antenna direction type	Omni-directional
Antenna features	Integrated antenna
Antennas quantity	2
Antenna gain level (max)	3 dBi
Performance	
Minimum system requirements	Microsoft Windows 10/8/7/Vista/XP
Certificates	
Compliance certificates	Federal Communications Commission (FCC), CE, RoHS
Certification	CE, FCC, RoHS
Weight & dimensions	
Width	180 mm

Depth	180 mm
Height	47.5 mm
Packaging data	
Package width	246 mm
Package depth	268 mm
Package height	69 mm
Package weight	600 g
Packaging content	
Quantity per pack	1 pc(s)
PoE adapter included	Yes
Mounting kit	Yes
Quick start guide	Yes
Operational conditions	
Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 90%
Sustainability	
Sustainability compliance	Yes
Logistics data	
Harmonized System (HS) code	85176990