

UBIQUITI NETWORKS .

Switch UPS 24+2P Ubiquiti UniFi USW-Pro-24-PoE 400W PoE++ M RM

SKU: 25011770 · EAN: 0817882027649

SPECIFIKAT TEKNIKE**56 specifikat e produktit**

ATRIBUTI	VLERA
Management features	
Switch type	Managed
Switch layer	L2/L3
Quality of Service (QoS) support	Yes
Web-based management	Yes
System event log	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
SFP+ module slots quantity	2
Power connector	AC-in jack
Network	
Networking standards	IEEE 802.3af, IEEE 802.3at
10G support	Yes
Port mirroring	Yes
Full duplex	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Rate limiting	Yes
IPv4 routes	64
VLAN support	Yes
Number of VLANs	1000
Data transmission	
Switching capacity	88 Gbit/s
Throughput	44000 Mpps
Forwarding rate	65.472 Mpps

MAC address table	16000 entries
Static route	Yes
Jumbo frames support	Yes
Packet buffer memory	2 MB
Security	
DHCP features	DHCP relay, DHCP server, DHCP snooping
IGMP snooping	Yes
Authentication type	IEEE 802.1x, RADIUS
Design	
Rack mounting	Yes
Form factor	1U
Product colour	Silver
Reset button	Yes
LED indicators	Activity, Link, PoE, Speed, System
Display type	LCM
Power	
Power source	AC
Power supply included	Yes
Redundant power supply (RPS) support	Yes
Number of power supply units	1
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (max)	450 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet plus (PoE+) ports quantity	16
Power over Ethernet 4PPoE (PoE++) ports quantity	8
Power over Ethernet (PoE) power per port	64 W
Total Power over Ethernet (PoE) budget	400 W
Operational conditions	
Operating temperature (T-T)	-5 - 40 °C
Operating relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width	442.4 mm
Depth	285.4 mm

Height	43.7 mm
Weight	4.3 kg
Certificates	
Certification	CE, FCC, IC
Logistics data	
Harmonized System (HS) code	85176990