

DELL

Monitor Dell Pro P2726HWO / 27"/ Full HD IPS LCD / 120Hz / 5ms / USB-C+HDMI+DP - Zezë

SKU: 16007700 · EAN: 5397321029502

SPECIFIKAT TEKNIKE

100 specifikat e produktit

ATRIBUTI	VLERA
Display	
Display diagonal	68.6 cm (27")
Display resolution	1920 x 1080 pixels
HD type	Full HD
Native aspect ratio	16:9
Display technology	LCD
Panel type	IPS
LED backlight	Yes
Backlight type	Edge LED
Touchscreen	No
Display brightness (typical)	300 cd/m ²
Response time	8 ms
Response time measurement type	GTG (Gray to Gray)
Anti-glare screen	Yes
Screen shape	Flat
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 720 (HD 720), 1280 x 1024 (SXGA), 1600 x 900, 1920 x 1080 (HD 1080)
Supported video modes	1080p, 720p, 576p, 480p
Contrast ratio (typical)	1500:1
Maximum refresh rate	120 Hz
Viewing angle. horizontal	178°
Viewing angle. vertical	178°
Display number of colours	16.7 million colours
Response time (fast)	5 ms
Pixel pitch	0.3114 x 0.3114 mm
Pixel density	82 ppi
Horizontal scan range	30 - 135 kHz

Vertical scan range	48 - 120 Hz
Viewable size. horizontal	59.8 cm
Viewable size. vertical	33.6 cm
Viewable size diagonal	68.6 cm
Surface hardness	3H
sRGB coverage (typical)	99%
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Flicker-free technology	Yes
Multimedia	
Built-in speaker(s)	No
Built-in camera	No
Design	
Product colour	Black
Ports & interfaces	
Built-in USB hub	Yes
USB hub version	2.0 / 3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-B
Number of downstream ports	4
Number of USB Type-B upstream ports quantity	1
USB Type-A downstream ports quantity	2
USB Type-C downstream ports quantity	2
HDMI	Yes
HDMI ports quantity	1
HDMI version	1.4
DisplayPorts quantity	1
DisplayPort version	1.4
Headphone out	No
HDCP	Yes
HDCP version	1.4
Charging port type	USB Type-C
Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm

Cable lock slot	Yes
Cable lock slot type	Kensington
Height adjustment	No
Pivot	Yes
Pivot angle	-90 - 90°
Swivelling	Yes
Swivel angle range	-45 - 45°
Tilt adjustment	Yes
Tilt angle range	-5 - 21°
On Screen Display (OSD)	Yes
Plug and Play	Yes
LED indicators	Yes
Power	
Energy efficiency class (SDR)	C
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	14 kWh
Power consumption (typical)	13.5 W
Power consumption (standby)	0.5 W
Power consumption (max)	74 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	5 - 90%
Operating altitude	0 - 5000 m
Non-operating altitude	0 - 12192 m
Weight & dimensions	
Width (without stand)	610.7 mm
Depth (without stand)	50 mm
Height (without stand)	354.7 mm
Weight (without stand)	4.36 kg

Bezel width (side)	6.4 mm
Bezel width (top)	6.4 mm
Bezel width (bottom)	1.2 cm
Packaging data	
Package weight	6.67 kg
USB cable length	1.8 m
Packaging content	
Stand included	Yes
Cables included	DisplayPort, HDMI, USB Type-A to USB Type-B, AC
DisplayPort cable length	1.8 m
HDMI cable length	1.8 m
Sustainability	
Sustainability certificates	ENERGY STAR, TCO
Doesn't contain	PVC/BFR, Mercury, Arsenic
Other features	
Compliance certificates	RoHS