

YEALINK

Telefon i thjeshtë Yealink W90DM - DECT-Manager

SKU: 12001541 · EAN: 6938818306202

SPECIFIKAT TEKNIKE	
69 specifikat e produktit	
ATRIBUTI	VLERA
Performance	
Number of handsets supported (max)	250
Number of carrier frequencies	2
Number of VoIP accounts	250
Management protocols	TFTP/FTP/HTTP/HTTPS/RPS
Supported network protocols	SIP v1 (RFC2543), v2 (RFC3261), SNTP/NTP, VLAN (802.1Q and 802.1P), 802.1x, LLDP, STUN, UDP/TCP/TLS
Number of bases supported (max)	60
Security algorithms	AES, HTTPS, SHA-384, SHA-512, SRTP, TLS
Wireless synchronization	Yes
Hearing aid compatibility	Yes
Dual-Tone Multi-Frequency (DTMF)	Yes
Keypad lock	Yes
XML browser	Yes
IPUI registration	Yes
User access level	Yes
Auto-provision	Yes
Over the Air Updates (OTA)	Yes
Call management	
Conference call	Yes
Number of parallel conferences	3
Phonebook capacity (per handset)	100 entries
Number of simultaneous calls (max)	100
Number of WB calls per base supported (max)	8
Number of NB calls per base supported (max)	8
Number of simultaneous calls per handset	2
Anonymous call	Yes
Anonymous call rejection	Yes

Call waiting	Yes
Call forwarding	Yes
Caller ID	Yes
Remote phonebook	Yes
Call transfer	Yes
Call hold	Yes
Do not disturb function	Yes
Switching between calls	Yes
Mute function	Yes
Speed dialling	Yes
Integrated voicemail	Yes
Redialing	Yes
Message Waiting Indication (MWI) function	Yes
Phonebook search/import/export function	Yes
Call history	Yes
Reset function	Yes
Emergency call	Yes
Shared Call Appearance (SCA)	Yes
System log export	Yes
Antenna	
Frequency range (EU)	1880 - 1900 MHz
Frequency range (US)	1920 - 1930 MHz
Maximum indoor range	50 m
Maximum outdoor range	300 m
Ports & interfaces	
Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rate supported (max)	100 Mbit/s
Design	
Product colour	White
Full duplex	Yes
Wall mountable	Yes
LED indicators	Yes
Power	
Input voltage	100 - 240 V
Power over Ethernet (PoE)	Yes

Output voltage	5 V
Output current	1.2 A
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 95%
Weight & dimensions	
Dimensions (WxDxH)	134 x 100 x 28 mm
Weight	2.8 kg
Package width	158 mm
Package depth	203 mm
Package height	63 mm
Package weight	3.4 kg
Logistics data	
Harmonized System (HS) code	85177900
Packaging content	
Quick start guide	Yes