

TP-LINK

Kamerë Sigurie IP CCTV TP-Link Omada VIGI C445, 2.8mm, 4MP, Full-Color Turret

SKU: 11006121 · EAN: 4895252506983

SPECIFIKAT TEKNIKE	
76 specifikat e produktit	
ATRIBUTI	VLERA
Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Infrared (IR) cut-off filter	Yes
Dynamic range	120 dB
Design	
Form factor	Turret
Mounting type	Ceiling/wall
Product colour	White
Housing material	Metal, Plastic
International Protection (IP) code	IP67
Camera	
Camera pan control	Yes
Camera tilt control	Yes
Minimum illumination	0.005 lx
Lens viewing angle. horizontal	100°
Lens viewing angle. vertical	54°
Lens viewing angle. diagonal	118°
Tilt angle range	0 - 85°
Pan range	0 - 360°
Camera shutter speed	1/3 - 1/10000 s
Number of Privacy masking areas	4
Image sensor	
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")

Progressive scan	Yes
Sensor type	CMOS
Lens system	
Number of lenses	1
Detect distance	64 m
Observe distance	27 m
Recognize distance	13 m
Lens diameter	2.8 mm
Focal length range	2.8 mm
Maximum aperture number	1.6
Identify distance	6 m
Minimum aperture number	1.6
Fixed focal length	2.8 mm
Night vision	
Night vision	Yes
Night vision distance	30 m
LED type	IR/White
Number of illumination LEDs	4
Infra-red wavelength	850 nm
Video	
Maximum resolution	2688 x 1520 pixels
Total megapixels	4 MP
Video compression formats	H.264, H.264+, H.265, H.265+
Supported graphics resolutions	1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2550 x 1440, 2688 x 1520
Frame rate	60 fps
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Bit rate control	Constant Bit Rate (CBR), Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Bit rate	6 Mbps
Region of Interest (ROI) encoding	Yes
Smart IR	Yes
Audio	
Built-in speaker(s)	Yes
Sample rate	8 kHz
Signal-to-Noise Ratio (SNR)	52 dB

Built-in microphone	Yes
Bit rate range	64 - 64 Kbit/s
Network	
Ethernet LAN	Yes
Ethernet interface type	Fast Ethernet
Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
DC-in jack	Yes
Security	
Password protection	Yes
IP address filtering	Yes
Privacy protection	Yes
Digest authentication	Yes
Power	
Power source type	DC, PoE
Power consumption (max)	10.1 W
Operational conditions	
Operating temperature (T-T)	-30 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Weight & dimensions	
Width	111 mm
Depth	111 mm
Height	83.7 mm
Weight	480 g
Packaging content	
Number of cameras	1