

LEVEL ONE

Konverter FVT-1105 10/100TX>100FX 80km

SKU: 25011890 · EAN: 4015867208076

SPECIFIKAT TEKNIKE**51 specifikat e produktit**

ATRIBUTI	VLERA
Network	
Maximum data transfer rate	100 Mbit/s
Converter input interface	10Base-T, 100Base-TX
Converter output interface	100Base-FX
Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
Ethernet interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Copper ethernet cabling technology	10BASE-T
Fiber ethernet cabling technology	100BASE-FX
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Store-and-forward	Yes
Duplex system	Full
Performance	
Maximum transfer distance	80000 m
Wavelength	1550 nm
Fiber mode structure	Single-mode
Fiber cable diameters supported (core/cladding)	50/125,62.5/125 µm
Mean time between failures (MTBF)	100000 h
Features	
Internal	Yes
LED indicators	Yes
Product colour	Black
Ports & interfaces	
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1

Fiber optic connector	SC
DC-in jack	Yes
Power	
Input voltage	5 V
Input current	1 A
Weight & dimensions	
Width	94 mm
Depth	71 mm
Height	26 mm
Weight	200 g
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	5 - 90%
Packaging content	
AC adapter included	Yes
Quick installation guide	Yes
Packaging data	
Package width	230 mm
Package depth	150 mm
Package height	58 mm
Package weight	300 g
Package type	Box
Certificates	
Compliance certificates	RoHS
Certification	CE
Logistics data	
Country of origin	China
Harmonized System (HS) code	85176990
Master (outer) case width	440 mm
Master (outer) case length	420 mm
Master (outer) case height	305 mm
Master (outer) case gross weight	32 kg
Products per master (outer) case	40 pc(s)