

NEOVO TECHNOLOGY .

Monitor AG Neovo TX-1502 / 15 3 / XGA VA LED Touch / 75 Hz / 5ms / HDMI + DP + VGA + USB - Zezë

SKU: 16007802 · EAN: 4710739597257

SPECIFIKAT TEKNIKE	
90 specifikat e produktit	
ATRIBUTI	VLERA
Display	
Display diagonal	38.1 cm (15")
Display resolution	1024 x 768 pixels
HD type	XGA
Native aspect ratio	4:3
Display technology	LED
Panel type	VA
Backlight type	LED
Touchscreen	Yes
Touchscreen type	Tabletop
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness (typical)	350 cd/m ²
Response time	5 ms
Anti-glare screen	Yes
Screen shape	Flat
Contrast ratio (typical)	800:1
Viewing angle. horizontal	160°
Viewing angle. vertical	150°
Display number of colours	16.78 million colours
Pixel pitch	0.297 x 0.297 mm
Horizontal scan range	31 - 61 kHz
Vertical scan range	55 - 75 Hz
Display diagonal (metric)	38.1 cm
Haze rate	25%
Surface hardness	7H

Colour gamut standard	NTSC
NTSC coverage (typical)	60%
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Operating hours (hours/days)	24/7
Operating system installed	Windows 10
Windows operating systems supported	Windows 10, Windows 7, Windows 8
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave
Linux operating systems supported	Yes
Multimedia	
Built-in speaker(s)	No
Built-in microphone	No
Built-in camera	No
Design	
Market positioning	Business
Product colour	Grey
Housing material	Metal
Detachable stand	Yes
Glass thickness	3.1 mm
Ports & interfaces	
Built-in USB hub	No
USB Touch port	Yes
USB Touch ports quantity	1
VGA (D-Sub) ports quantity	1
HDMI	Yes
HDMI ports quantity	1
HDMI version	1.4
DisplayPorts quantity	1
Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
Cable lock slot	Yes
Cable lock slot type	Kensington

Height adjustment	No
Tilt adjustment	Yes
Tilt angle range	-5 - 90°
Plug and Play	Yes
LED indicators	Yes
Power	
Power consumption (typical)	8 W
Power consumption (standby)	0.6 W
Power consumption (off)	0.3 W
AC adapter output voltage	12 V
Power supply type	External
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width (with stand)	348.4 mm
Depth (with stand)	214.2 mm
Height (with stand)	312.7 mm
Weight (with stand)	4.6 kg
Width (without stand)	348.4 mm
Depth (without stand)	46.6 mm
Height (without stand)	276.4 mm
Weight (without stand)	2.7 kg
Packaging data	
Package width	415 mm
Package depth	290 mm
Package height	370 mm
Package weight	7 kg
Packaging content	
Stand included	Yes
Cables included	AC, HDMI, USB, VGA
Sustainability	
Sustainability compliance	Yes

Other features	
International Protection (IP) code	IP65
Mobile operating systems supported	Android
Compliance certificates	CE, REACH, RoHS, WEEE
Certification	CE, LVD, WEEE, RoHS, REACH,EAC
Logistics data	
Harmonized System (HS) code	85285210