

LENOVO

Monitor LENOVO ThinkVision P34WD 40 / 34"/ Wide Quad HD IPS / LED / Curved / 120 Hz / 6 ms / USB + HDMI + DisplayPort – Gri

SKU: 16007846 · EAN: 0198156243645

SPECIFIKAT TEKNIKE

106 specifikat e produktit

ATRIBUTI	VLERA
Display	
Display diagonal	86.4 cm (34")
Display resolution	3440 x 1440 pixels
HD type	Wide Quad HD
Native aspect ratio	21:9
Display technology	LCD
Panel type	IPS
LED backlight	Yes
Backlight type	W-LED
Touchscreen	No
Display brightness (typical)	350 cd/m²
Response time	6 ms
Anti-glare screen	Yes
Screen shape	Curved
Screen curvature rating	3800R
Contrast ratio (typical)	2000:1
Contrast ratio (dynamic)	3000000:1
Maximum refresh rate	120 Hz
Viewing angle. horizontal	178°
Viewing angle. vertical	178°
Display number of colours	1.07 billion colours
Response time (fast)	4 ms
Pixel pitch	0.2325 x 0.2325 mm
Pixel density	110 ppi
Viewable size. horizontal	80 cm
Viewable size. vertical	33.5 cm

High Dynamic Range (HDR) supported	Yes
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)
Colour depth	10 bit
Colour gamut standard	DCI-P3, sRGB
Colour gamut	98%
sRGB coverage (typical)	99%
DCI-P3 coverage	98%
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Low Blue Light technology	Yes
Windows operating systems supported	Windows 10, Windows 11
Multimedia	
Number of speakers	2
RMS rated power	6 W
Built-in speaker(s)	Yes
Built-in microphone	No
Built-in camera	No
Design	
Product colour	Black
Colour name	Eclipse Black
Ports & interfaces	
Built-in USB hub	Yes
USB upstream port type	USB Type-B, USB Type-C
Number of upstream ports	2
Number of USB Type-B upstream ports quantity	1
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	5
USB Type-C downstream ports quantity	2
USB Type-C DisplayPort Alternate Mode	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	140 W
HDMI	Yes
HDMI ports quantity	1
HDMI version	2.1
DisplayPorts quantity	2

DisplayPort out quantity	1
DisplayPort out version	1.4
DisplayPort version	1.4
Network	
Ethernet LAN	Yes
Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Cable lock slot	Yes
Cable lock slot type	Kensington
Height adjustment	Yes
Adjustable height (max)	15.5 cm
Swivelling	Yes
Swivel angle range	-45 - 45°
Tilt adjustment	Yes
Tilt angle range	-5 - 23.5°
On Screen Display (OSD)	Yes
Power	
Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	G
Energy consumption (SDR) per 1000 hours	26 kWh
Energy consumption (HDR) per 1000 hours	43 kWh
Power consumption (typical)	28 W
Power consumption (standby)	0.5 W
Power consumption (max)	250 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Weight & dimensions	
Width (with stand)	817.1 mm
Depth (with stand)	220 mm
Height (with stand)	548.8 mm
Weight (with stand)	10 kg
Width (without stand)	817.1 mm

Depth (without stand)	82.2 mm
Height (without stand)	358.6 mm
Weight (without stand)	7.2 kg
Bezel width (side)	2 mm
Bezel width (top)	2 mm
Bezel width (bottom)	1.27 cm
Packaging data	
Package width	905 mm
Package depth	174 mm
Package height	470 mm
Package weight	14.7 kg
Packaging content	
Stand included	Yes
Cables included	DisplayPort, Power, USB Type-A to USB Type-B, USB Type-C to USB Type-C
DisplayPort cable length	1.8 m
Power cable length	1.8 m
Sustainability	
Sustainability certificates	ENERGY STAR, EPEAT Gold, TCO
Other features	
Ethernet LAN (RJ-45) ports	1
Certification	ENERGY STAR Certified, TCO 10, TCO Edge 2.1, EPEAT GoldEyesafe Display 2.0, TÜV Low Blue Light (Hardware solution), TÜV In-Plane Switching Black, TÜV Rheinland Flicker Free, TÜV Rheinland Eye Comfort (5 Stars)