

TP-LINK

Access Point TP LINK / Omada EAP115 Wall

SKU: 25011970 · EAN: 6935364093457

SPECIFIKAT TEKNIKE	
60 specifikat e produktit	
ATRIBUTI	VLERA
Features	
2.4 GHz	Yes
5 GHz	No
6 GHz	No
Maximum data transfer rate	300 Mbit/s
Maximum data transfer rate (2.4 GHz)	300 Mbit/s
Ethernet LAN data rates	10,100 Mbit/s
Frequency band	2.4 - 2.4835 GHz
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Cabling technology	10/100Base-T(X)
Automatic channel selection	Yes
Wi-Fi Multimedia (WMM)/(WME)	Yes
VLAN support	Yes
Virtual LAN features	Port-based VLAN, VLAN mapping
Rate limiting	Yes
Wireless isolation	Yes
Quality of Service (QoS) support	Yes
Transmitting power (CE)	20 dBm
Transmitting power	15 dBmW
Security	
Security algorithms	802.1x RADIUS, HTTPS, WPA, WPA-PSK, WPA2, WPA2-PSK
MAC address filtering	Yes
Service Set Identifier (SSID) features	Multiple SSIDs
Number of SSID supported	8
Access Control List (ACL)	Yes
Protocols	
Management protocols	SNMP, Telnet

Management features	
Web-based management	Yes
Syslog	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
WAN connection	Ethernet (RJ-45)
Power	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	Passive PoE
Power consumption (typical)	2.8 W
Design	
Placement	Wall
Product colour	White
Cable lock slot	No
Reset button	Yes
LED indicators	Yes
Internal	No
Antenna	
Antenna type	Internal
Antenna direction type	Omni-directional
Antenna features	Integrated antenna
Antennas quantity	2
Antenna gain level (max)	1.8 dBi
Performance	
Compatible operating systems	Windows XP, Windows Vista, Windows 7, Windows 8, Windows 10
Certificates	
Compliance certificates	CE, RoHS
Weight & dimensions	
Width	86.8 mm
Depth	86.8 mm
Height	30.2 mm
Packaging data	
Package width	118 mm
Package depth	130 mm
Package height	47 mm

Package weight	190 g
Packaging content	
Quantity per pack	1 pc(s)
Mounting kit	Yes
Quick start guide	Yes
Operational conditions	
Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 90%
Sustainability	
Sustainability compliance	Yes
Logistics data	
Harmonized System (HS) code	85176990