

DELL

Monitor Dell P2425DE / 24 3 / QHD IPS LCD / 100 Hz / 5ms / HDMI + DP + USB - Zezë

SKU: 16007870 · EAN: 5397184962466

SPECIFIKAT TEKNIKE

112 specifikat e produktit

ATRIBUTI	VLERA
Display	
Display diagonal	61 cm (24")
Display resolution	2560 x 1440 pixels
HD type	Quad HD
Native aspect ratio	16:9
Display technology	LCD
Panel type	IPS
LED backlight	Yes
Backlight type	Edge LED
Touchscreen	No
Display brightness (typical)	250 cd/m ²
Response time	8 ms
Response time measurement type	GTG (Gray to Gray)
Anti-glare screen	Yes
Screen shape	Flat
Supported video modes	480p, 576p, 720p, 1080i, 1080p, 1440p
Contrast ratio (typical)	1500:1
Maximum refresh rate	100 Hz
Viewing angle. horizontal	178°
Viewing angle. vertical	178°
Display number of colours	16.7 million colours
Response time (fast)	5 ms
Pixel pitch	0.2058 x 0.2058 mm
Pixel density	123 ppi
Viewable size. horizontal	52.7 cm
Viewable size. vertical	29.6 cm
Digital horizontal frequency	30 - 150 kHz

Digital vertical frequency	48 - 100 Hz
Surface hardness	3H
sRGB coverage (typical)	99%
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Flicker-free technology	Yes
Low Blue Light technology	Yes
Multimedia	
Built-in speaker(s)	No
Built-in camera	No
Design	
Market positioning	Office
Product colour	Black
Ports & interfaces	
Built-in USB hub	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-C
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	3
USB Type-C downstream ports quantity	1
USB Type-C DisplayPort Alternate Mode	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	90 W
HDMI	Yes
HDMI ports quantity	1
HDMI version	2.1
DisplayPorts quantity	1
DisplayPort out quantity	1
DisplayPort version	1.4
Headphone out	No
HDCP	Yes
HDCP version	1.4
Network	
Ethernet LAN	Yes

Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
Cable lock slot	Yes
Cable lock slot type	Kensington
Height adjustment	Yes
Adjustable height (max)	15 cm
Pivot	Yes
Pivot angle	-90 - 90°
Swivelling	Yes
Swivel angle range	-45 - 45°
Tilt adjustment	Yes
Tilt angle range	-5 - 21°
On Screen Display (OSD)	Yes
Plug and Play	Yes
LED indicators	Yes
Power	
Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	17 kWh
Power consumption (typical)	16.5 W
Power consumption (standby)	0.3 W
Power consumption (max)	185 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	5 - 90%
Operating altitude	0 - 5000 m
Non-operating altitude	5000 - 12191 m

Weight & dimensions	
Width (with stand)	538.7 mm
Depth (with stand)	181.5 mm
Height (with stand)	496.6 mm
Weight (with stand)	5.25 kg
Width (without stand)	538.7 mm
Depth (without stand)	49.7 mm
Height (without stand)	315.2 mm
Weight (without stand)	3.78 kg
Packaging data	
Package weight	7.57 kg
Packaging content	
Stand included	Yes
Cables included	AC, DisplayPort, USB Type-A to USB Type-C, USB Type-C to USB Type-C
DisplayPort cable length	1.8 m
Sustainability	
Sustainability certificates	ENERGY STAR, TCO
Doesn't contain	Arsenic, Mercury, PVC/BFR
Carbon footprint	
Total carbon footprint (kg of CO2e)	187
Carbon emissions, manufacturing (kg of CO2e)	86.39
Carbon emissions, logistics (kg of CO2e)	14.21
Carbon emissions, energy usage (kg of CO2e)	80.97
Carbon emissions, end-of-life (kg of CO2e)	5.24
PAIA version	GaBi version 1, 2024
Other features	
RJ-45 ports quantity	1
Compliance certificates	RoHS
Packaging content	USB-C to C 10Gbps, 100W cable - 1.00 m