

LEVEL ONE

LevelOne GES-2105P 5-Port Gigabit PoE+ Switch, 4-Port PoE+, 60W Budget, Smart Lite Managed, Hilbert Series

SKU: 25012006 · EAN: 4015867229194

SPECIFIKAT TEKNIKE**78 specifikat e produktit**

ATRIBUTI	VLERA
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	5
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Port mirroring	Yes
Full duplex	Yes
Half duplex	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Rate limiting	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
MAC address auto-learning supported	Yes
MAC address auto-aging supported	Yes
VLAN support	Yes
Virtual LAN features	Tagged VLAN
Number of VLANs	32

Data transmission	
Switching capacity	10 Gbit/s
MAC address table	2000 entries
Number of queues	4
Jumbo frames support	Yes
Jumbo frames	9000
Packet buffer memory	1.5 MB
Security	
IGMP snooping	Yes
Multicast features	
Multicast support	Yes
Design	
Product colour	Black
LED indicators	Yes
Performance	
Flash memory	2 MB
Noise level	0 dB
Mean time between failures (MTBF)	43800 h
Power	
Power source	DC/PoE
Power supply included	Yes
Input current	1.2 A
Input voltage	54 V
Power consumption (max)	65 W
Surge protection	Yes
Surge protection voltage	8 kV
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet plus (PoE+) ports quantity	4
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	60 W
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%

Storage relative humidity (H-H)	5 - 95%
Heat dissipation	23.88 BTU/h
Weight & dimensions	
Width	160 mm
Depth	95 mm
Height	29 mm
Weight	400 g
Packaging content	
Cables included	AC
Quick start guide	Yes
Packaging data	
AC adapter included	Yes
Package type	Box
Package width	310 mm
Package depth	230 mm
Package height	65 mm
Package weight	920 g
Sustainability	
Sustainability compliance	Yes
Technical details	
Master (outer) cases per pallet (air)	18 pc(s)
Pallet gross length	80 cm
Pallet gross width	120 cm
Pallet height (air)	158.4 cm
Certificates	
Compliance certificates	CE, RoHS
Certification	UKCA, FCC Class A
Logistics data	
Master (outer) case net weight	600 g
Country of origin	China
Master (outer) case width	350 mm
Master (outer) case length	330 mm
Master (outer) case height	480 mm
Master (outer) case gross weight	9.8 kg
Products per master (outer) case	10 pc(s)