

THERMALTAKE

Furnizues Energjie (PSU) 1200W Thermaltake Toughpower GT 1200W ATX3.1/GEN5 80+G Zezë

SKU: 17010672 · EAN: 4711658544087

SPECIFIKAT TEKNIKE

46 specifikat e produktit

ATRIBUTI	VLERA
Power	
Total power	1200 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Input current	15 - 10 A
Power Factor Correction (PFC) type	Active
Combined power (+3.3V)	100 W
Combined power (-12V)	1200 W
Combined power (+5V)	100 W
Combined power (-12V)	3.6 W
Combined power (+5Vsb)	15 W
Max output current (+3.3V)	20 A
Max output current (-12V)	100 A
Max output current (+5V)	20 A
Max output current (-12V)	0.3 A
Max output current (+5Vsb)	3 A
Hold time	17 ms
Power protection features	Over current, Over power, Under voltage, Over voltage, Short circuit
Ports & interfaces	
Motherboard power connector	24-pin ATX
Motherboard power cable length	55 cm
Number of SATA power connectors	6
SATA power cable length	150,450 mm
Peripheral (Molex) power connectors (4-pin)	4
Peripheral (Molex) power cable length	150,400 mm
EPS power connector (4+4 pin)	Yes
PCI Express power connectors (6+2 pin)	5

PCI Express power connectors (12+4 pin)	2
PCI Express power connectors (12+4 pin) cable length	600 mm
Cabling type	Fully-Modular
Performance	
80 PLUS certification	80 PLUS Gold
Purpose	PC
Power supply unit (PSU) form factor	ATX
ATX version	3.1
Bearing technology	Hydraulic
Mean time between failures (MTBF)	100000 h
Design	
Product colour	Black
Cooling type	Active
Fan diameter	12 cm
Number of fans	1 fan(s)
On/off switch	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 85%
Certificates	
Compliance certificates	BIS, BSMI, CB, CCC, CE, EAC, Federal Communications Commission (FCC), ICES, Low Voltage Directive (LVD), RCM, UKCA, cTUVus
Weight & dimensions	
Width	150 mm
Depth	140 mm
Height	86 mm