

APC

APC BV500I-GR Easy UPS 500VA / 300W – Line-Interactive UPS 230V with AVR & 4x Schuko Sockets

SKU: 26010873 · EAN: 0731304338284

SPECIFIKAT TEKNIKE

46 specifikat e produktit

ATRIBUTI	VLERA
Features	
UPS topology	Line-Interactive
Output power capacity	0.5 kVA
Output power	300 W
Waveform	Sine
Input operation voltage (min)	170 V
Input operation voltage (max)	280 V
Input frequency	50/60 Hz
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Surge energy rating	156 J
Transfer time (Line Mode to Battery Mode)	6 ms
Number of input phases	1
Number of output phases	1
Noise level	40 dB
Surge protection	Yes
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	Type F
AC outlets quantity	4 AC outlet(s)
SmartSlot	No
SmartConnect port	No
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	4.5 Ah
Battery voltage	12 V

Battery recharge time	8 h
Cold start	Yes
Design	
Form factor	Compact
Cable length	1.52 m
Product colour	Black
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 90%
Operating altitude	0 - 1968.3 m
Certificates	
Compliance certificates	RoHS
Certification	CEREACH
Packaging content	
Management card included	No
Weight & dimensions	
Width	160 mm
Depth	305 mm
Height	92 mm
Weight	3.9 kg
Packaging data	
Package width	373 mm
Package depth	143 mm
Package height	237 mm
Package weight	4.2 kg
Logistics data	
Harmonized System (HS) code	85078000
Other features	
Nominal output voltage	230 V