

AXIS

Kamerë Sigurie IP CCTV Axis Cube M1055-L Box 1080p

SKU: 11006203 · EAN: 7331021076228

SPECIFIKAT TEKNIKE	
60 specifikat e produktit	
ATRIBUTI	VLERA
Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Infrared (IR) cut-off filter	Yes
Number of languages	12
Languages support	Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese, Korean, Polish, Portuguese, Russian
Certification	EN 55032 Class A, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), KS C 9832 Class A, KS C 9835, RCM AS/NZS CISPR 32 Class A, VCCI Class A
Design	
Form factor	Box
Mounting type	Ceiling/wall
Product colour	White
LED indicators	Yes
Housing material	Aluminium, Plastic
Camera	
Minimum illumination	0.03 lx
Lens viewing angle. horizontal	103°
Lens viewing angle. vertical	55°
Camera shutter speed	1/19000 s
Image sensor	
Number of sensors	1
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")
Sensor type	CMOS
Lens system	

Number of lenses	1
Fixed focal length	3.16 mm
Night vision	
Night vision	Yes
Video	
Maximum resolution	1920 x 1080 pixels
Video compression formats	AVC, H.264, H.265, HEVC, M-JPEG
Supported graphics resolutions	320 x 240, 640 x 360, 1280 x 960, 1920 x 1080 (HD 1080)
Supported video modes	1080p
Frame rate	30 fps
Video intelligence analytic	Yes
Video streaming	Yes
Image quality adjustment	Brightness, Colour depth, Contrast, Saturation, Sharpness
Privacy masking	Yes
Text caption overlay	Yes
Bit rate control	Variable Bit Rate (VBR)
Network	
Ethernet LAN	Yes
Networking standards	IEEE 802.1x
Supported network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS, HTTP/2, TLS, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP® , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, NTP, NTS, RTSP, RTCP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, DHCPv4/v6, SSH, LLDP, MQTT v3.1.1, Syslog, Link-Local-Adresse (ZeroConf)
Quality of Service (QoS) support	Yes
Storage	
Built-in HDD	No
Compatible memory cards	MicroSD (TransFlash), MicroSDHC
Flash memory	512 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Security	
IP address filtering	Yes
Security algorithms	EAP-TLS, HTTPS, SNMP
Power	
Power source type	PoE
Power consumption (typical)	2.2 W

Power consumption (max)	4.3 W
Power consumption (Power over Ethernet (PoE))	4.3 W
DC output voltage	12
DC output current	2.5 A
Operational conditions	
Operating temperature (T-T)	0 - 35 °C
Storage temperature (T-T)	-40 - 65 °C
Operating relative humidity (H-H)	10 - 85%
Storage relative humidity (H-H)	5 - 95%
Weight & dimensions	
Width	60 mm
Depth	93 mm
Height	105 mm
Weight	137 g
Packaging content	
Number of cameras	1