

AXIS

Kamerë Sigurie IP CCTV Axis Mini Fix Dome M4215-LV 4MP

SKU: 11006224

SPECIFIKAT TEKNIKE	
78 specifikat e produktit	
ATRIBUTI	VLERA
Performance	
Type	IP security camera
Placement supported	Indoor
Connectivity technology	Wired
PTZ control	Yes
PTZ modes	Digital PTZ
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Infrared (IR) cut-off filter	Yes
Built-in processor	Yes
Number of languages	19
Languages support	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Italian, Japanese, Korean, Russian, Swedish, Thai, Turkish, Vietnamese
Certification	CSA, UL/cUL, BIS, UKCA, CE, KC, EAC, VCCI, RCM
Design	
Form factor	Dome
Mounting type	Ceiling/wall
Product colour	White
Housing material	Aluminium, Polycarbonate (PC)
International Protection (IP) code	IP42
IK code	IK08
Camera	
Camera pan control	Yes
Camera tilt control	Yes
Minimum illumination	0.14 lx
Angle of rotation	105°
Lens viewing angle. horizontal	93 - 47°
Lens viewing angle. vertical	50 - 26°

Tilt angle range	-40 - 65°
Pan range	-180 - 180°
Camera shutter speed	1/25000 - 1/5 s
Image sensor	
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")
Progressive scan	Yes
Sensor type	CMOS
Lens system	
Zoom capability	Yes
Maximum aperture number	2.6
Minimum aperture number	1.7
Night vision	
Night vision	No
Video	
Maximum resolution	1920 x 1080 pixels
Total megapixels	2 MP
Video compression formats	H.264, H.265, M-JPEG
Video recording	Yes
Frame rate	30 fps
Video streaming	Yes
Noise reduction	Yes
Noise reduction technology	2D noise reduction, 3D noise reduction
Privacy masking	Yes
Network	
Ethernet LAN	Yes
Ethernet interface type	Fast Ethernet
Networking standards	IEEE 802.1x, IEEE 802.3af, IEEE 802.3at
Supported network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS, TLS, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCP, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Link-Local address (ZeroConf)
Wi-Fi	No
Bluetooth	No
Quality of Service (QoS) support	Yes
Storage	
Built-in HDD	No

Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash), MicroSDHC, MicroSDXC
Flash memory	512 MB
Internal memory	1024 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
HDMI ports quantity	1
Security	
Password protection	Yes
Video motion detection	Yes
Active tampering alarm	Yes
IP address filtering	Yes
Mirror	Yes
Pixel counter	Yes
Digest authentication	Yes
Network access storage (NAS)	Yes
Power	
Power source type	PoE
Power consumption (max)	9.5 W
Power consumption (Power over Ethernet (PoE))	4.8 W
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-30 - 65 °C
Operating relative humidity (H-H)	10 - 85%
Storage relative humidity (H-H)	5 - 95%
Weight & dimensions	
Height	71 mm
Diameter	12 cm
Weight	366 g
Packaging content	
Number of cameras	1
Manual	Yes
Packaging content	Owner authentication key, virtual client license for H.264/H.265