

GRANDSTREAM

Access Point Grandstream DP752 DECT Basisstation - Pika e Qasjes Grandstream DP752 Stacioni Bazë DECT

SKU: 25012191 · EAN: 6947273702733

SPECIFIKAT TEKNIKE	
28 specifikat e produktit	
ATRIBUTI	VLERA
Performance	
Number of handsets supported (max)	5
Maximum range	400 m
Comfort noise generation (CNG)	Yes
Supported network protocols	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP/RARP, ICMP, DNS (A, SRV, NAPTR), DHCP, PPPoE, SSH, TFTP, NTP, STUN, SIMPLE, LLDP-MED, LDAP, TR-069, 802.1x, TLS, SRTP
Security algorithms	256-bit AES, HTTPS, MD5, SRTP, SSL/TLS
Voice codecs	AJB, AMR-WB, CNG, G.711alaw, G.711ulaw, G.722, G.722.2, G.723.1, G.726-32, G.729A, G.729B, OPUS, PLC, VAD, iLBC
Quality of Service (QoS) support	Yes
Firmware upgradeable	Yes
Compatible products	Grandstream Networks DP730, DP722, DP720
Call management	
Conference call	Yes
Number of parallel conferences	3
Call waiting	Yes
Call forwarding	Yes
Call transfer	Yes
Call hold	Yes
Do not disturb function	Yes
Ports & interfaces	
Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	1
Design	
Product colour	Black
Certification	FCC: FCC 15B; FCC 15D; MPE; FCC IDCE: EN 55032; EN 55035; EN 61000-3-2; EN 61000-3-3; EN 60950-1; EN 301 489-1/-6; EN301 406; EN 50385; RED NB CertRCM: AS/NZS 32; AS/NZS 60950.1ANATEL: ANATEL, EAC, UL

Power	
Power over Ethernet (PoE)	Yes
Operational conditions	
Operating temperature (T-T)	-10 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 90%
Weight & dimensions	
Dimensions (WxDxH)	64.98 x 105 x 140.31 mm
Weight	140 g
Package weight	370 g
Logistics data	
Harmonized System (HS) code	85177900