

IIYAMA

Monitor IIYAMA XU2492HSU B6 – 23.8" / IPS / Full HD / I zi

SKU: 16008247 · EAN: 4948570122585

SPECIFIKAT TEKNIKE	
84 specifikat e produktit	
ATRIBUTI	VLERA
Display	
Display diagonal	60.5 cm (23.8")
Display resolution	1920 x 1080 pixels
HD type	Full HD
Native aspect ratio	16:9
Display technology	LED
Panel type	IPS
Touchscreen	No
Display brightness (typical)	250 cd/m²
Response time (MPRT)	0.4 ms
Display surface	Matt
Screen shape	Flat
Contrast ratio (typical)	1300:1
Contrast ratio (dynamic)	80000000:1
Maximum refresh rate	100 Hz
Viewing angle. horizontal	178°
Viewing angle. vertical	178°
Display number of colours	16.7 million colours
Response time (fast)	0.4 ms
Pixel pitch	0.275 x 0.275 mm
Horizontal scan range	30 - 115 kHz
Viewable size. horizontal	52.7 cm
Viewable size. vertical	29.6 cm
Display diagonal (metric)	60.5 cm
sRGB coverage (typical)	99%
NTSC coverage (typical)	72%
Performance	
NVIDIA G-SYNC	No

AMD FreeSync	Yes
AMD FreeSync type	FreeSync
Flicker-free technology	Yes
Low Blue Light technology	Yes
Multimedia	
Number of speakers	2
RMS rated power	4 W
Built-in speaker(s)	Yes
Built-in camera	No
Design	
Market positioning	Home
Product colour	Black
Ports & interfaces	
Built-in USB hub	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
Number of downstream ports	4
USB Type-A downstream ports quantity	4
HDMI	Yes
HDMI ports quantity	1
DisplayPorts quantity	1
Headphone out	Yes
Headphone outputs	1
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Cable management	Yes
Cable lock slot	Yes
Cable lock slot type	Kensington
Height adjustment	No
Tilt adjustment	Yes
Tilt angle range	2 - 22°
On Screen Display (OSD) languages	Czech, German, English, Spanish, French, Italian, Japanese, Dutch, Polish, Portuguese, Russian
Power	
Energy efficiency class (SDR)	D

Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	13.2 kWh
Power consumption (typical)	0 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Weight & dimensions	
Width (with stand)	539.5 mm
Depth (with stand)	199.5 mm
Height (with stand)	415 mm
Weight (with stand)	3.4 kg
Packaging data	
Package width	610 mm
Package depth	130 mm
Package height	410 mm
Package weight	4.9 kg
Packaging content	
Cables included	AC, USB, HDMI, DisplayPort
Quick start guide	Yes
Sustainability	
Sustainability certificates	ErP, TCO
Other features	
User controls	picture adjust (contrast, brightness, i-Style colour, ACR, Eco, OD, X-Res technology), image settings (blue light reducer, sharp&soft, video mode adjust), colour settings (gamma, 6-axis, colour temp.), audio settings (volume, mute), OSD settings (OSD H. position, OSD V. position, OSD time, language), extra1 (MBR, AdaptiveSync, USB BC), extra2 (reset, DDC/CI, signal select, HDMI range, opening logo, LED, information)
Packaging content	quick start guide, safety guide
Weight	3.4 kg
Height	415 mm
Width	539.5 mm
Depth	199.5 mm
Control panel	Signal Select / Exit, + / Volume, - / Eco +, Menu , Power
Compliance certificates	CE, EAC, PSE, REACH, RoHS, TÜV mark, UKCA, VCCI, WEEE

