

AJA

Konvertues Video AJA OG-ROI-SDI, 3G-SDI në 3G-SDI dhe HDMI 1.4, ROI Scaling, Frame Rate Conversion, 1080p60, Audio 24-bit, openGear - Zezë

SKU: 26028133 · EAN: 0812321032352

SPECIFIKAT TEKNIKE	
26 specifikat e produktit	
ATRIBUTI	VLERA
Video	
Type	openGear Scan Converter card
Standard	3G-SDI to 3G-SDI / HDMI
Video input	1x 3G-SDI BNC, SMPTE-259/292/424
Max Input Format	1920x1080p 60 Hz
Video outputs	1x 3G-SDI BNC (loop through), 1x 3G-SDI BNC (SMPTE-259/292/424), 1x HDMI Type A v1.4
Supported input formats	SD (525i/625i), HD (720p, 1080i, 1080p), 3G
Scaling	Region of Interest (ROI)
Conversion	Up, down, cross-conversion; aspect ratio; frame rate; H/V flip; 90° rotation
Deinterlacing	Yes (Deinterlaced to Progressive)
Loss of Input	Black, Freeze, or Mute
Color range	Full, SMPTE
Genlock / Reference Input	Reference Input, SDI Input, Free Run; 1080i/1080p/720p tri-level sync, 625i/525i Color Black, 75 ohm terminating
Audio	
Audio input digital	24-bit, 16-channel embedded SDI
Audio output digital	24-bit, 16-channel embedded SDI; 24-bit, 8-channel HDMI
Audio output analog	2x 3-pin terminal block, 2-channel balanced
Features	
Form factor	openGear standard (front slot + rear card, two slots required)
Hot-swap	Yes
Compatible frames	OG-X-FR, OG-3-FR, DFR-8321
Remote control	Ethernet, via Ross DashBoard (Windows, macOS, Linux)
Warranty	5 years
Power	
Power consumption	7 W max per card

Operational conditions	
Operating temperature	0 to 40°C (32 to 104°F)
Storage temperature	-40 to 60°C (-40 to 140°F)
Operating humidity	10 to 90% non-condensing
Max operating altitude	3,000 m (10,000 ft)
Weight & dimensions	
Weight	0.5 lb (0.3 kg)