

OPTOMA

Projektor Optoma HZ40HDR / DLP Laser / 4000 Lumen / Full HD / 16:9 / 3D - Bardhë

SKU: 18000725 · EAN: 5055387667624

SPECIFIKAT TEKNIKE	
74 specifikat e produktit	
ATRIBUTI	VLERA
Projector	
Supported aspect ratios	4:3, 16:10, 16:9
Screen size compatibility	508 - 7620 mm (20 - 300")
Projection distance	0.8 - 10 m
Contrast ratio (dynamic)	2000000:1
Projector brightness	4000 ANSI lumens
Projection technology	DLP
Projector native resolution	1080p (1920x1080)
Contrast ratio (typical)	300000:1
Native aspect ratio	16:9
Number of colours	1.073 billion colours
Uniformity	75%
Horizontal scan range	15 - 140 kHz
Vertical scan range	24 - 120 Hz
Keystone correction. horizontal	-30 - 30°
Keystone correction. vertical	-30 - 30°
Light source	
Light source type	Laser
Service life of light source	30000 h
Lens system	
Focal length range	12.81 - 16.74 mm
Zoom type	Manual
Zoom ratio	1.1:1
Throw ratio	1.48:1 ~ 1.62:1
Offset	116%
Video	

Analog signal format system	NTSC J, NTSC M, PAL B, PAL D, PAL G, PAL H, PAL I, PAL M, PAL N, SECAM B, SECAM D, SECAM G, SECAM K, SECAM K1, SECAM L
Full HD	Yes
3D	Yes
Supported graphics resolutions	640 x 480 (VGA), 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 768 (WXGA), 1280 x 800 (WXGA), 1600 x 1200 (UXGA), 1920 x 1080 (HD 1080)
Supported video modes	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video colour modes	Game
Ports & interfaces	
HDMI version	2.0
USB 2.0 ports quantity	1
Headphone outputs	1
Serial interface type	RS-232
HDMI ports quantity	2
DVI port	No
Network	
Ethernet LAN	No
Storage	
Card reader integrated	No
Features	
On Screen Display (OSD)	Yes
Number of OSD languages	25
Noise level	32 dB
High Dynamic Range (HDR) supported	Yes
Password protection	Yes
Multimedia	
Built-in speaker(s)	Yes
RMS rated power	15 W
Number of built-in speakers	1
Design	
Market positioning	Portable
Product type	Standard throw projector
Product colour	White
Cable lock slot	Yes
Cable lock slot type	Kensington

Display	
Built-in display	No
Power	
Power source	AC
Power consumption (typical)	88 W
Power consumption (standby)	0.5 W
Power consumption (max)	139 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Auto power off	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 80%
Operating altitude	0 - 2500 m
Weight & dimensions	
Width	274 mm
Depth	216 mm
Height	114 mm
Weight	3 kg
Package width	400 mm
Package depth	280 mm
Package height	160 mm
Package weight	4.2 kg
Packaging content	
Remote control included	Yes
Batteries included	Yes
Cables included	AC
Manual	Yes
Logistics data	
Export Control Classification Number (ECCN)	EAR99
Harmonized System (HS) code	8528.62