

EIZO

Monitor EIZO EV2795-WT / 27 3 / WQHD IPS LED / 60Hz / 5ms / USB + HDMI + DP + USB-C - Bardhë

SKU: 16008305 · EAN: 4995047056645

SPECIFIKAT TEKNIKE

106 specifikat e produktit

ATRIBUTI	VLERA
Display	
Display diagonal	68.6 cm (27")
Display resolution	2560 x 1440 pixels
HD type	Quad HD
Native aspect ratio	16:9
Display technology	LCD
Panel type	IPS
LED backlight	Yes
Backlight type	W-LED
Touchscreen	No
Display brightness (typical)	350 cd/m ²
Response time	5 ms
Anti-glare screen	Yes
Screen shape	Flat
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1600 x 1200 (UXGA), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 2560 x 1440
Contrast ratio (typical)	1000:1
Maximum refresh rate	60 Hz
Viewing angle. horizontal	178°
Viewing angle. vertical	178°
Display number of colours	16.78 million colours
Pixel pitch	0.233 x 0.233 mm
Pixel density	109 ppi
Viewable size. horizontal	59.7 cm
Viewable size. vertical	33.6 cm
Viewable size diagonal	68.5 cm
Digital horizontal frequency	31 - 89 kHz

Digital vertical frequency	59 - 61 Hz
Colour gamut standard	sRGB
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Flicker-free technology	Yes
Low Blue Light technology	Yes
Multimedia	
Number of speakers	2
RMS rated power	2 W
Built-in speaker(s)	Yes
Built-in camera	No
Design	
Market positioning	Office
Product colour	White
Feet colour	White
Ports & interfaces	
Built-in USB hub	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-B, USB Type-C
Number of upstream ports	2
Number of USB Type-B upstream ports quantity	1
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	3
USB Type-C downstream ports quantity	1
USB Type-C DisplayPort Alternate Mode	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	70 W
HDMI	Yes
HDMI ports quantity	1
DisplayPorts quantity	1
Headphone out	Yes
Headphone outputs	1
Headphone connectivity	3.5 mm
Built-in KVM switch	Yes
HDCP	Yes

Network	
Ethernet LAN	Yes
Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Cable lock slot	Yes
Cable lock slot type	Kensington
Height adjustment	Yes
Adjustable height (max)	17.7 cm
Pivot	Yes
Pivot angle	-90 - 90°
Swivelling	Yes
Swivel angle range	0 - 344°
Tilt adjustment	Yes
Tilt angle range	-5 - 35°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	German, English, Spanish, French, Italian, Swedish
Power	
Energy efficiency class (SDR)	D
Energy consumption (SDR) per 1000 hours	16 kWh
Power consumption (typical)	16.1 W
Power consumption (standby)	0.5 W
Power consumption (max)	164 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Energy efficiency scale	A to G
European Product Registry for Energy Labelling (EPREL) code	356881
Operational conditions	
Operating temperature (T-T)	5 - 35 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width (with stand)	611 mm
Depth (with stand)	230 mm

Height (with stand)	369 mm
Weight (with stand)	8.5 kg
Width (without stand)	611 mm
Depth (without stand)	56 mm
Height (without stand)	357 mm
Weight (without stand)	5.7 kg
Packaging content	
Stand included	Yes
Cables included	AC, USB Type-C to USB Type-C
Quick start guide	Yes
Sustainability	
Sustainability compliance	Yes
Sustainability certificates	ENERGY STAR, EPEAT Climate +, EPEAT Gold, TCO
Other features	
Automatic brightness control	Yes
Warranty period	5 year(s)
Look-up table (LUT) bit depth	14
Compliance certificates	CB, CCC, CE, China RoHS, Federal Communications Commission (FCC), GS mark, ICES, PSE, RCM, RoHS, cTUVus, UKCA, VCCI, WEEE
Ethernet LAN data rates	10,100,1000 Mbit/s
Ethernet LAN (RJ-45) ports	1
Certification	CE, UKCA, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), TCO Certified Generation 10, EPEAT 2018 (US), TÜV/Blue Low Light Content, TÜV/Flicker Free, RCM, cTUVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA ENERGY STAR, RoHS, WEEE, China RoHS, CCC
Logistics data	
Harmonized System (HS) code	85285210