

CANON

Printer Canon i-SENSYS LBP325x / Mono Laser Printer

SKU: 19010522 · EAN: 4549292133851

SPECIFIKAT TEKNIKE	
71 specifikat e produktit	
ATRIBUTI	VLERA
Printing	
Duplex printing mode	Auto
Colour	No
Print technology	Laser
Duplex printing	Yes
Maximum resolution	600 x 600 DPI
Print speed (black. normal quality. A4/US Letter)	43 ppm
Warm-up time	30 s
Time to first page (black. normal)	5.7 s
Print margins (top. bottom. right. left)	5 mm
Secure printing	Yes
Features	
Maximum duty cycle	150000 pages per month
Recommended duty cycle	2000 - 7500 pages per month
Printing colours	Black, White
Page description languages	PCL 5e, PCL 6, PostScript 3, UFR II
Number of printer fonts	241
Input & output capacity	
Total number of input trays	1
Total input capacity	550 sheets
Total output capacity	150 sheets
Paper input type	Cassette, Paper tray
Multi-Purpose tray	Yes
Multi-Purpose tray input capacity	100 sheets
Maximum number of input trays	4
Maximum input capacity	2300 sheets
Paper handling	
Maximum ISO A-series paper size	A4

Paper tray media types	Bond paper, Envelopes, Heavy paper, Labels, Plain paper, Postcard, Recycled paper
Multi-purpose tray media types	Envelopes
ISO A-series sizes (A0...A9)	A4, A5, A6
ISO B-series sizes (B0...B9)	B5
Envelopes sizes	C5, Com-10, DL, Monarch
Custom media width	105 - 216 mm
Custom media length	148 - 355.6 mm
Paper tray media weight	60 - 120 g/m²
Multi-Purpose Tray media weight	60 - 199 g/m²
Duplex media weight	60 - 120 g/m²
Ports & interfaces	
USB port	Yes
USB 2.0 ports quantity	1
Network	
Network ready	Yes
Wi-Fi	No
Ethernet LAN	Yes
Cabling technology	10/100/1000Base-T(X)
Ethernet LAN data rates	10,100,1000 Mbit/s
Mobile printing technologies	Apple AirPrint, Canon PRINT Business, Google Cloud Print, Mopria Print Service
Performance	
Internal memory	1024 MB
Built-in processor	Yes
Processor frequency	528 MHz
Sound pressure level (printing)	69 dB
Design	
Market positioning	Business
Product colour	White
Built-in display	Yes
Display	LCD
Display number of lines	5 lines
Power	
Power consumption (printing)	600 W
Power consumption (max)	1380 W

Power consumption (standby)	10.1 W
Power consumption (PowerSave)	1.2 W
Energy Star Typical Electricity Consumption (TEC)	1.5 kWh/week
AC input voltage	220 - 240 V
AC input frequency	50 - 60 Hz
System requirements	
Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Vista
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.9 Mavericks
Linux operating systems supported	Yes
Server operating systems supported	Windows Server 2003, Windows Server 2003 R2, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Operational conditions	
Operating temperature (T-T)	10 - 30 °C
Operating relative humidity (H-H)	20 - 80%
Weight & dimensions	
Width	417 mm
Depth	376 mm
Height	330 mm
Weight	11.5 kg
Logistics data	
Harmonized System (HS) code	84433210
Other features	
Printer management	Department ID Management, Remote User Interface, iW Management Console, eMaintenance, uniFLOW
Acoustic pressure emissions	54 dB