

LEVEL ONE

Kamerë sigurie IP LevelOne Gemini FCS-5212Z bullet 6MP me zoom 4× / IR dhe PoE

SKU: 11006334 · EAN: 4015867229569

SPECIFIKAT TEKNIKE

90 specifikat e produktit

ATRIBUTI	VLERA
Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Infrared (IR) cut-off filter	No
Design	
Form factor	Bullet
Mounting type	Floor/wall
Product colour	White
LED indicators	Activity, Link, Power
Protection features	Vandal proof
International Protection (IP) code	IP66
IK code	IK10
Weatherproof	Yes
Country of origin	China
Camera	
Minimum illumination	0 lx
Lens viewing angle. horizontal	32 - 106°
Lens viewing angle. vertical	18 - 56°
Lens viewing angle. diagonal	37 - 127°
Camera shutter speed	1/3 - 1/100000 s
Image sensor	
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")
Progressive scan	Yes
Sensor type	CMOS

Lens system	
Zoom capability	Yes
Optical zoom	4.3x
Focal length range	2.8 - 12 mm
Night vision	
Night vision	Yes
Night vision distance	60 m
LED type	IR
Video	
Maximum resolution	3200 x 1800 pixels
Total megapixels	6 MP
Video compression formats	H.264, H.265, M-JPEG
Supported graphics resolutions	640 x 360, 640 x 480 (VGA), 1280 x 720 (HD 720), 2688 x 1520, 3200 x 1800
Frame rate	30 fps
Video streaming	Yes
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Image quality adjustment	Brightness, Contrast, Saturation, Sharpness
Privacy masking	Yes
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Audio	
Audio system	2-way
Voice codecs	G.711, G.722.1, G.726, MP2L2, PCM
Network	
Ethernet LAN	Yes
Networking standards	IEEE 802.3at
Wi-Fi	No
Bluetooth	No
Number of simultaneous live view channels	3 channels
Storage	
Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSDHC, MicroSDXC
Maximum memory card size	256 GB

Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Terminal block port	Yes
Security	
Video motion detection	Yes
Active tampering alarm	Yes
Intelligent Video Surveillance (IVS) system features	Crossing line, Face detection, Intrusion
Mirror	Yes
Human and vehicle targets classification	Yes
Power	
Power source type	DC, PoE
Power consumption (max)	13 W
Power consumption (Power over Ethernet (PoE))	15 W
DC output voltage	12
DC output current	1.08 A
Operational conditions	
Operating temperature (T-T)	-30 - 60 °C
Storage temperature (T-T)	-30 - 70 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Weight & dimensions	
Width	100 mm
Depth	300 mm
Height	80 mm
Weight	1.89 kg
Packaging data	
Package width	190 mm
Package depth	180 mm
Package height	385 mm
Package weight	2.01 kg
Package type	Box
Sustainability	
Sustainability compliance	Yes
Compliance certificates	CE, Federal Communications Commission (FCC)

Packaging content	
Number of cameras	1
Screws included	Yes
Logistics data	
Master (outer) cases per pallet (air)	12 pc(s)
Pallet gross length	80 cm
Pallet gross width	120 cm
Pallet height (air)	168.8 cm
Harmonized System (HS) code	8525890000
Master (outer) case width	560 mm
Master (outer) case length	405 mm
Master (outer) case height	590 mm
Master (outer) case gross weight	19 kg
Products per master (outer) case	9 pc(s)