

HEWLETT PACKARD ENTERPRISE

Server HPE DL380 Gen11 2U XEON 4510 2x32GB 2x8TB LFF MR408i-o 2x1000W

SKU: 99043119 · EAN: 0190017720463

SPECIFIKAT TEKNIKE

45 specifikat e produktit

ATRIBUTI	VLERA
Processor	
Processor manufacturer	Intel
Processor family	Intel Xeon Silver
Processor model	4510
Processor frequency	2.4 GHz
Processor cores	12
Processor cache	30 MB
Number of processors installed	1
Processor cache type	L3
Memory	
Internal memory	64 GB
Internal memory type	DDR5-SDRAM
Memory clock speed	5600 MHz
Memory layout (slots x size)	2 x 32 GB
Storage	
Maximum storage capacity	91.2 TB
Total storage capacity	16 TB
Number of HDDs installed	2
HDD interface	SATA III
SSD interface	SATA III
RAID support	Yes
RAID levels	0, 1, 5, 6, 10, 50, 60
Supported RAID controllers	HPE MR416i-p Gen11 x16 Lanes 8GB Cache PCI SPDM Plug-in Storage Controller
Hot-Plug support	Yes
Optical drive type	No
Graphics	

On-board graphics card	Yes
Maximum graphics card memory	16 MB
Network	
LAN controller	Broadcom BCM5719
Ethernet LAN	Yes
Ethernet interface type	Gigabit Ethernet
Ports & interfaces	
Ethernet LAN (RJ-45) ports	4
Expansion slots	Up to 8 PCIe Gen5, and 2 OCP 3.0, for detailed descriptions reference the QuickSpecs
Design	
Chassis type	Rack (2U)
Rack mounting	Yes
Performance	
Management platform	HPE iLO Standard with intelligent provisioning (embedded), and HPE Compute Ops Management (optional subscription available)
Trusted Platform Module (TPM)	Yes
Trusted Platform Module (TPM) version	2.0
Software	
Operating system installed	No
Power	
Power supply type	2x HPE 1000W Flex Slot Titanium Hot Plug Power Supply Kit
Redundant power supply (RPS) support	Yes
Power supply	1000 W
Number of redundant power supplies supported	2
Number of redundant power supplies installed	1
Number of main power supplies	2
Other features	
Standard fans	6x Standard Fans
Storage drive type	2x HPE 8TB SATA 6G Business Critical 7.2K LFF LP 1-year Warranty 512e Multi Vendor HDD
Security features	HPE TPM 2.0 standard on motherboard. Optional locking Bezel Kit, Intrusion Detection Kit. For full security features refer to the QuickSpecs.
Number of processors supported	1