

HONEYWELL

# Skaner Honeywell Vuquest 3320G / 2D / USB / Cable inkl

SKU: 19010686 · EAN: 4016139164137

| SPECIFIKAT TEKNIKE                 |                             |
|------------------------------------|-----------------------------|
| 27 specifikat e produktit          |                             |
| ATRIBUTI                           | VLERA                       |
| <b>Scanning</b>                    |                             |
| Type                               | Fixed bar code reader       |
| Optical sensor resolution          | 838 pixels                  |
| Scanner type                       | 1D/2D                       |
| Sensor type                        | Photo diode                 |
| Linear (1D) barcodes supported     | PDF417                      |
| Light levels (direct sunlight)     | 0 - 100000 lx               |
| Pitch reading angle                | -45 - 45°                   |
| Yaw reading angle                  | -65 - 65°                   |
| <b>Ports &amp; interfaces</b>      |                             |
| Connectivity technology            | Wired                       |
| Standard interfaces                | RS-232, USB, Keyboard wedge |
| <b>Performance</b>                 |                             |
| International Protection (IP) code | IP53                        |
| LED indicators                     | Yes                         |
| Product colour                     | Ivory                       |
| <b>Power</b>                       |                             |
| Power source type                  | DC                          |
| Power consumption (typical)        | 2.3 W                       |
| Power consumption (standby)        | 0.45 W                      |
| Input voltage                      | 5 V                         |
| Power consumption                  | 450 mA                      |
| <b>Weight &amp; dimensions</b>     |                             |
| Width                              | 51 mm                       |
| Depth                              | 73 mm                       |
| Height                             | 26 mm                       |
| Weight                             | 77 g                        |

|                                   |             |
|-----------------------------------|-------------|
| <b>Packaging data</b>             |             |
| Cables included                   | USB         |
| <b>Operational conditions</b>     |             |
| Operating temperature (T-T)       | 0 - 40 °C   |
| Storage temperature (T-T)         | -20 - 70 °C |
| Operating relative humidity (H-H) | 5 - 95%     |
| <b>Logistics data</b>             |             |
| Harmonized System (HS) code       | 84716070    |