

ASROCK

Pllakë Amë MB Server ASRock Mainboard GENOA2D24G-2L+ Proprietary Dual Socket SP5 Single

SKU: 17012307 · EAN: 4711430521053

SPECIFIKAT TEKNIKE**46 specifikat e produktit**

ATRIBUTI	VLERA
Processor	
Processor manufacturer	AMD
Processor socket	Socket SP5
Compatible processor series	AMD EPYC
Maximum number of SMP processors	2
Memory	
Supported memory types	DDR5-SDRAM
Number of memory slots	24
Memory slots type	DIMM
Memory slot pin count	288
Memory voltage	1.1 V
Supported memory clock speeds	4800 MHz
Maximum internal memory	12 TB
Storage controllers	
Supported storage drive types	HDD & SSD
Supported storage drive interfaces	SATA III
Number of HDDs supported	32
Number of storage drives supported	34
Graphics	
Parallel processing technology support	Not supported
On-board graphics card model	Aspeed AST2600
On-board graphics card memory	512 MB
Internal I/O	
USB 3.2 Gen 1 (3.1 Gen 1) connectors	2
Front panel connector	Yes
ATX Power connector (24-pin)	Yes
Number of chassis fan connectors	6

Chassis intrusion connector	Yes
Number of COM connectors	1
Rear panel I/O ports	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4
Ethernet LAN (RJ-45) ports	2
IPMI LAN (RJ-45) port	Yes
VGA (D-Sub) ports quantity	1
Network	
Ethernet LAN	Yes
Ethernet interface type	Gigabit Ethernet
LAN controller	Intel® I350
Wi-Fi	No
Features	
Motherboard chipset	AMD SoC
Product colour	Green, Grey
PC health monitoring	Fan, Temperature, Voltage
Component for	Server
Motherboard chipset family	AMD
BIOS	
BIOS type	UEFI AMI
ACPI version	6.4
Clear CMOS button	Yes
System Management BIOS (SMBIOS) version	3.5
Operational conditions	
Storage temperature (T-T)	10 - 35 °C
Operating temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	20 - 90%
Weight & dimensions	
Width	430 mm
Depth	350 mm