

NOCTUA

# Ftohës për Kasë Noctua NF-A8 5V PWM, 80mm - Kafe

SKU: 17020975 · EAN: 9010018100310

| SPECIFIKAT TEKNIKE            |                                                                                                                 |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------|
| 28 specifikat e produktit     |                                                                                                                 |
| ATRIBUTI                      | VLERA                                                                                                           |
| <b>Cooling</b>                |                                                                                                                 |
| Fan size                      | 80 x 80 x 25 mm                                                                                                 |
| Connector                     | 4-pin PWM                                                                                                       |
| Rated voltage                 | 5 V                                                                                                             |
| Rotational speed (max)        | 2200 rpm                                                                                                        |
| Rotational speed (min)        | 450 rpm                                                                                                         |
| Airflow (max)                 | 55.5 m³/h (32.67 CFM)                                                                                           |
| Static pressure (max)         | 2.37 mm H2O                                                                                                     |
| Acoustical noise (max)        | 17.7 dB(A)                                                                                                      |
| Bearing type                  | SSO2                                                                                                            |
| Blade geometry                | A-Series, Flow Acceleration Channels                                                                            |
| Anti-vibration pads           | Yes, silicone rubber                                                                                            |
| Mounting hole spacing         | 71.5 x 71.5 mm                                                                                                  |
| Cable length                  | 200 mm + 300 mm extension                                                                                       |
| MTTF                          | > 150,000 h                                                                                                     |
| <b>Power</b>                  |                                                                                                                 |
| Input power (max.)            | 0.75 W                                                                                                          |
| Input current (max)           | 0.15 A                                                                                                          |
| <b>Operational conditions</b> |                                                                                                                 |
| Operating temperature         | -10°C to +70°C                                                                                                  |
| Operating humidity            | 15 - 90%                                                                                                        |
| IP rating                     | IP50                                                                                                            |
| <b>Packaging content</b>      |                                                                                                                 |
| Included accessories          | 30 cm extension cable, 4x anti-vibration mounts, USB power adaptor cable, OmniJoin adaptor cable, 4x fan screws |
| <b>Packaging data</b>         |                                                                                                                 |
| Package dimensions (HxWxD)    | 210 x 150 x 34 mm                                                                                               |
| Package weight                | 250 g                                                                                                           |

|                                |                           |
|--------------------------------|---------------------------|
| <b>Logistics data</b>          |                           |
| Quantity per master case       | 40 pcs                    |
| Master case dimensions (HxWxD) | 390 x 375 x 360 mm        |
| Master case weight             | 11,500 g                  |
| <b>Certificates</b>            |                           |
| Certifications                 | CE, UKCA, UL, RoHS, REACH |
| <b>Technical details</b>       |                           |
| Frame material                 | PBT GF30                  |
| Warranty                       | 6 years                   |