

TP-LINK

Access Point TP Link Omada EAP787 / BE12000 / Tri Band Wi-Fi 7 Ceiling - Bardhë

SKU: 25012589 · EAN: 1210002600569

SPECIFIKAT TEKNIKE	
45 specifikat e produktit	
ATRIBUTI	VLERA
Features	
2.4 GHz	Yes
5 GHz	Yes
6 GHz	Yes
Maximum data transfer rate (2.4 GHz)	688 Mbit/s
Maximum data transfer rate (5 GHz)	8648 Mbit/s
Maximum data transfer rate (6 GHz)	5765 Mbit/s
Frequency band	2.4 - 6 GHz
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11be, IEEE 802.11g, IEEE 802.11n
Coverage area	1750 m ²
Number of users	510 user(s)
Bluetooth	Yes
Automatic channel selection	Yes
Automatic channel scanning	Yes
MIMO	Yes
MIMO type	Multi User MIMO
VLAN support	Yes
Rate limiting	Yes
Flow control support	Yes
Band steering	Yes
Airtime Fairness (ATF)	Yes
Quality of Service (QoS) support	Yes
BeamForming	Yes
Security	
Security algorithms	WPA, WPA2, WPA3
Access Control List (ACL)	Yes

Ports & interfaces	
DC-in jack	Yes
Power	
Power over Ethernet (PoE)	Yes
DC voltage range	12 V
Input current	2.5 A
Design	
Placement	Ceiling, Wall
Product colour	White
Reset button	Yes
LED indicators	Yes
Antenna	
Antenna type	Internal
Certificates	
Certification	CE, FCC, RoHS, IC
Weight & dimensions	
Width	220 mm
Depth	220 mm
Height	38.8 mm
Packaging data	
Package type	Box
Packaging content	
Quantity per pack	1 pc(s)
Mounting kit	Yes
Quick start guide	Yes
Operational conditions	
Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 90%