

HIKVISION

Kamerë Sigurie IP CCTV Hikvision DS-2CD2746G2H-IPTRZS2U/SL, 4MP, 2.8–12mm, PTRZ Motorike, AcuSense, DarkFighter, WDR 120dB, IR 40m, Audio, Stroboskop, PoE+, IP66, IK10 - Zezë

SKU: 26028288 · EAN: 6942160497792

SPECIFIKAT TEKNIKE

37 specifikat e produktit

ATRIBUTI	VLERA
Camera	
Model	DS-2CD2746G2H-IPTRZS2U/SL(2.8-12)BLK
Image sensor	1/1.8" Progressive Scan CMOS
Max. resolution	2688 x 1520 (4 MP)
Min. illumination	Color 0.0008 Lux (F1.2, AGC ON), B/W 0 Lux with IR
Shutter time	1/3 s - 1/100,000 s
WDR	120 dB
Day/Night	IR cut filter (ICR)
Remote adjustment (PTRZ)	Pan 0°-350°, Tilt 0°-85°, Rotate 0°-350°
Lens system	
Lens type	Varifocal, motorized, 2.8-12 mm
Aperture	Max. F1.2
Horizontal FOV	114.6° - 41.8°
Vertical FOV	59.3° - 23.6°
Diagonal FOV	141.3° - 48.1°
Night vision	
IR range	40 m
IR wavelength	850 nm
Video	
Compression	H.265+, H.265, H.264+, H.264
Main stream frame rate	25 fps (2688x1520, 1920x1080, 1280x720)
Bit rate	32 Kbps - 16 Mbps
Audio	
Built-in microphone	Arrayed dual-microphone
Built-in speaker	1, max. power 2 W, sound pressure level 97 dB (at 10 cm)

Features	
Active deterrence	Strobe light + siren
Face Capture	Yes
AcuSense	Human and vehicle classification
Storage	
On-board storage	microSD/microSDHC/microSDXC, up to 512 GB
Network	
Ethernet interface	1x RJ45, 10/100 Mbps self-adaptive
Protocols	ONVIF (Profile S, G, T), ISAPI, SDK
Power over Ethernet (PoE)	
PoE standard	IEEE 802.3at, Class 4, max. 18 W
Power	
Power supply	12 VDC ± 25%, 1.35 A, max. 16 W
Design	
Form factor	Dome
Material	Metal
Color	Black
Dimensions	Ø155 mm x 140.4 mm
Weight & dimensions	
Weight	approx. 840 g
Operational conditions	
Storage temperature	-30°C - 60°C
Humidity	95% or less (non-condensing)
Security	
IP rating	IP66
Impact protection	IK10