

TELTONIKA

Ruter Industrial Teltonika RUT145, Wi-Fi 4, 2× RJ45 10/100Mbps, RS485, DIN Rail - Zezë

SKU: 26031927 · EAN: 4779051846771

SPECIFIKAT TEKNIKE	
68 specifikat e produktit	
ATRIBUTI	VLERA
WAN connection	
Feature	Ethernet WAN
WAN connection type	RJ-45
Wireless LAN features	
Wi-Fi band	Single-band (2.4 GHz)
Top Wi-Fi standard	Wi-Fi 4 (802.11n)
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Network	
Feature	Ethernet LAN
Ethernet LAN interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Cabling technology	10/100Base-T(X)
Networking standards	IEEE 802.11w, IEEE 802.11s, IEEE 802.11r, IEEE 802.11v, IEEE 802.11k, IEEE 802.3, IEEE 802.3u, IEEE 802.3az, IEEE 802.11e, IEEE 802.1x
Feature	Auto MDI/MDI-X
Feature	Port forwarding
Feature	Load balancing system
Feature	Dynamic DNS (DDNS)
Feature	Policy-based routing
Feature	Static route
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
RS-485 ports	1
Management features	
Feature	Web-based management
Feature	Wi-Fi Multimedia (WMM)/(WME)
Feature	Quality of Service (QoS) support

Feature	Wake-on-LAN ready
Feature	Reset button
Feature	Cloud-managed
Feature	Backup function
Security	
Security algorithms	WPA2-Enterprise-PEAP, WPA2-PSK, WPA-EAP, WPA-PSK, WPA3-SAE, WPA3-EAP, OWE, AES-CCMP, TKIP, EAP-TLS
Feature	Firewall
Feature	DoS attack prevention
Feature	MAC address filtering
Feature	URL filtering
Feature	System event log
Feature	DMZ support
Feature	Network address translation (NAT)
Protocols	
Feature	DHCP client
Feature	DHCP server
Feature	Universal Plug and Play (UPnP)
Design	
Product colour	Black
Housing material	Aluminium
International Protection (IP) code	IP30
LED indicators	WAN, LAN, Power
Product type	Industrial router
Certificates	
Compliance certificates	UKCA, CB, RCM, Federal Communications Commission (FCC), Industry Canada (IC), EAC, WEEE, CE
Packaging content	
Cables included	Power
Feature	Quick start guide
Antenna	
Antenna design	External
Antenna connector type	RP-SMA
Antennas quantity	1
Features	
Feature	Built-in processor

Processor manufacturer	MediaTek
Processor architecture	MIPS 24KEc
Processor frequency	580 MHz
Internal memory	128 MB
Internal memory type	DDR2
Flash memory	16 MB
Number of simultaneously connected devices (max)	50
Operating system installed	RutOS
Feature	Firmware upgradeable
Power	
Power source type	DC
Output voltage	9 - 30 V
Feature	Power over Ethernet (PoE)
Operational conditions	
Operating temperature (T-T)	-40 - 75 °C
Operating relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width	113.1 mm
Depth	68.6 mm
Height	25 mm
Weight	140 g
Packaging data	
Number of products included	1 pc(s)
Logistics data	
Harmonized System (HS) code	851762