

TELTONIKA

Ruter Teltonika TRB255 / Dual SIM / LTE / Industrial

SKU: 25012739 · EAN: 4779027312767

SPECIFIKAT TEKNIKE	
29 specifikat e produktit	
ATRIBUTI	VLERA
Design	
Product colour	Grey
LED indicators	Power
Protocols	
Management protocols	SNMP
Supported network protocols	TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, FTP, SMTP, SSL v3, TLS, ARP, PPP (planned), UPNP (planned), SSH, DHCP, Telnet, MQTT (planned), Wake On Lan (WOL) (planned)
DMZ support	Yes
Network	
Ethernet LAN data rates	10,100 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3u
Dynamic DNS (DDNS)	Yes
Security	
Firewall security	Yes
Authentication method	Pre-shared key, digital certificates, X.509 certificates
DoS attack prevention	Yes
Network address translation (NAT)	Yes
Ports & interfaces	
RS-232 ports	1
Ethernet LAN (RJ-45) ports	1
Serial interface type	RS-232/485
Management features	
Quality of Service (QoS) support	Yes
Universal Plug and Play (UPnP)	Yes
Reset button	Yes
Weight & dimensions	
Width	83 mm
Depth	25 mm

Height	74 mm
Weight	165 g
Packaging content	
Manual	Yes
Quick installation guide	Yes
Operational conditions	
Operating temperature (T-T)	-40 - 75 °C
Storage temperature (T-T)	10 - 90 °C
Certificates	
Safety	IEC 62368-1:2014, EN 50385:2017, EN 62232:2017
Certification	CE/RED, EAC, RoHS, WEEE Draft ETSI EN 301 489-1 V2.2.0, Draft EN 301 489-19 V2.1.0, Draft ETSI EN 301 489-52 V1.1.0 EN 61000-4-2:2009 EN 300 511 V12.5.1, ETSI EN 301 908-1 V11.1.1, ETSI EN 301 908-2 V11.1.2, ETSI EN 301 908-13 V11.1.2 EN 61000-4-3:2006 + A1:2008 + A2:2010 EN 61000-4-4:2012 EN 61000-4-5:2014 EN 61000-4-6:2014 EN 61000-4-11:2004
Logistics data	
Harmonized System (HS) code	85176990