

TRENDNET

Switch Industrial TRENDnet TI-G102, 8x Gigabit Ethernet RJ45, 2x Gigabit RJ45/SFP Combo, 20Gbps, IP30, DIN-Rail - Zezë

SKU: 26030686 · EAN: 0710931160925

SPECIFIKAT TEKNIKE**35 specifikat e produktit**

ATRIBUTI	VLERA
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	10
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
SFP+ module slots quantity	2
Power connector	DC-in jack
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
Feature	Full duplex
Feature	Auto-negotiation
Feature	MAC address auto-learning supported
Feature	MAC address auto-aging supported
Data transmission	
Switching capacity	20 Gbit/s
Forwarding rate	14.8 Mpps
MAC address table	16000 entries
Feature	Store-and-forward
Design	
Product colour	Black
Housing material	Metal
LED indicators	Yes
International Protection (IP) code	IP30
Feature	Wall mountable
Feature	DIN rail mounting
Performance	
Buffer size	2048 KB
Mean time between failures (MTBF)	510400 h

Power	
Feature	Redundant power supply (RPS) support
DC input voltage	12 - 56 V
Input voltage	12/56 V
Power consumption (max)	5.76 W
Operational conditions	
Operating temperature (T-T)	-40 - 75 °C
Operating relative humidity (H-H)	0 - 95%
Weight & dimensions	
Width	155 mm
Depth	120 mm
Height	48 mm
Weight	415 g
Packaging data	
Feature	Wall mounting kit
Feature	Terminal block included
Certificates	
Certification	CE, FCC
Logistics data	
Harmonized System (HS) code	85176990