

NETGEAR

NETGEAR GS724TP 24-Port Gigabit PoE+ Smart Managed Switch L3 Lite with 2x SFP 190W

SKU: 25012804 · EAN: 0606449162660

SPECIFIKAT TEKNIKE

66 specifikat e produktit

ATRIBUTI	VLERA
Management features	
Switch type	Managed
Switch layer	L2/L3/L4
Quality of Service (QoS) support	Yes
Web-based management	Yes
System event log	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
SFP+ module slots quantity	2
Power connector	DC-in jack
Network	
Networking standards	IEEE 802.1D, IEEE 802.1ab, IEEE 802.1as, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3x, IEEE 802.3z
10G support	Yes
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 100BASE-TX, 1000BASE-T
Port mirroring	Yes
Full duplex	Yes
IP routing	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Spanning tree protocol	Yes
VLAN support	Yes
Number of VLANs	64
Optical fiber	
Fiber ethernet cabling technology	1000BASE LX, 1000BASE SX

Data transmission	
Switching capacity	52 Gbit/s
MAC address table	8000 entries
Store-and-forward	Yes
Number of queues	8
Number of static routes	32
Jumbo frames support	Yes
Jumbo frames	9216
Packet buffer memory	0.512 MB
Security	
DHCP features	DHCP client
Access Control List (ACL)	Yes
IGMP snooping	Yes
Security algorithms	802.1x RADIUS, HTTPS, SSL/TLS
MAC address filtering	Yes
SSH/SSL support	Yes
Multicast features	
Multicast support	Yes
Number of multicast groups filtered	128
Protocols	
Management protocols	SNMP v1/v2/v3
Design	
Rack mounting	Yes
Stackable	Yes
Product colour	Blue
LED indicators	Activity, Link, Speed
Number of fans	3 fan(s)
Performance	
Noise level	0 dB
Firmware upgradeable	Yes
Mean time between failures (MTBF)	634966 h
Power	
Power supply included	Yes
AC input voltage	100 - 240 V
Power consumption (max)	446.7 W

Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Total Power over Ethernet (PoE) budget	380 W
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	0 - 90%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Weight & dimensions	
Width	440 mm
Depth	204 mm
Height	43 mm
Weight	3.7 kg
Packaging content	
Cables included	AC
Quick start guide	Yes
User guide	Yes
Manual	Yes
Certificates	
Certification	CE, FCC, VCCI, EN, C-Tick, CCC, CSA, UL/cUL, IEC