

LEVEL ONE

Kamerë sigurie LevelOne FCS-3402 IP 2MP për jashtë me IR dhe PoE

SKU: 11006449 · EAN: 4015867231289

SPECIFIKAT TEKNIKE	
92 specifikat e produktit	
ATRIBUTI	VLERA
Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Day/night mode	Yes
Infrared (IR) cut-off filter	Yes
Certification	CE, FCC
Design	
Form factor	Dome
Mounting type	Ceiling/wall
Product colour	White
LED indicators	Power
Protection features	Dust resistant, Heat resistant, Rain proof, Snow resistant, Vandal proof
International Protection (IP) code	IP67
IK code	IK10
Weatherproof	Yes
Country of origin	China
Camera	
Minimum illumination	0 lx
Field of view (FOV) angle	86°
Lens viewing angle. vertical	46°
Lens viewing angle. diagonal	102°
Camera shutter speed	1/3 - 1/100000 s
Image sensor	
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")
Progressive scan	Yes
Sensor type	CMOS

Lens system	
Zoom capability	Yes
Digital zoom	8x
Number of lenses	1
Focus adjustment	2.0
Fixed focal length	4 mm
Night vision	
Night vision	Yes
Night vision distance	30 m
LED type	IR
Infra-red wavelength	850 nm
Video	
Maximum resolution	1920 x 1080 pixels
Total megapixels	2 MP
Video formats supported	H.264, H.265, M-JPEG
Supported graphics resolutions	320 x 240, 640 x 360, 640 x 480 (VGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)
Frame rate	30 fps
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Image quality adjustment	Brightness, Contrast, Saturation, Sharpness
Privacy masking	Yes
Back Light Compensation (BLC)	Yes
Region of Interest (ROI) encoding	Yes
Network	
Ethernet LAN	Yes
Ethernet interface type	Fast Ethernet
Networking standards	IEEE 802.1x, IEEE 802.3, IEEE 802.3af, IEEE 802.3u
Supported network protocols	TCP(IPv6/v4), UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, DNS, DDNS, NTP, ICMP, ARP, IGMP,SMTP,FTP,SAMBA UPnP, SNMP, Bonjour
Wi-Fi	No
Bluetooth	No
Number of users	32 user(s)
Storage	
Built-in HDD	No
Card reader integrated	Yes

Compatible memory cards	MicroSDHC, MicroSDXC
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Microphone in	Yes
Headphone outputs	1
Terminal block port	Yes
DC-in jack	Yes
Security	
Password protection	Yes
Video motion detection	Yes
Active tampering alarm	Yes
Anti-flicker	Yes
Heartbeat	Yes
Mirror	Yes
Digital watermark	Yes
Management features	
Reset button	Yes
Power	
Power source type	DC, PoE
Power consumption	400 mA
Power consumption (max)	5 W
Power consumption (Power over Ethernet (PoE))	7 W
Operational conditions	
Operating temperature (T-T)	-30 - 60 °C
Operating relative humidity (H-H)	0 - 95%
System requirements	
Mobile operating systems supported	Android, iOS
Weight & dimensions	
Depth	82 mm
Diameter	11.1 cm
Weight	500 g
Packaging data	
Package width	134 mm
Package depth	111 mm
Package height	108 mm

Package weight	502 g
Package type	Box
Sustainability	
Compliance certificates	RoHS
Packaging content	
Number of cameras	1
Screws included	Yes
Resource CD	Yes
Other features	
Browser supported	IIE7+, Chrome18-42, Firefox5.0+, Safari5.02+
Logistics data	
Harmonized System (HS) code	85258900
Master (outer) case width	111 mm
Master (outer) case length	111 mm
Master (outer) case height	111 mm
Master (outer) case gross weight	608 g
Products per master (outer) case	24 pc(s)