

DELL

Monitor Dell UltraSharp U4021QW / 39.7"/ 4K DCI IPS / LCD / 60 Hz / 8 ms / HDMI+USB+DP / Curved - Argjend

SKU: 16008689 · EAN: 5397184409633

SPECIFIKAT TEKNIKE

108 specifikat e produktit

ATRIBUTI	VLERA
Display	
Display diagonal	100.8 cm (39.7")
Display resolution	5120 x 2160 pixels
HD type	4K DCI
Native aspect ratio	21:9
Display technology	LCD
Panel type	IPS
Backlight type	LED
Touchscreen	No
Display brightness (typical)	300 cd/m ²
Response time	8 ms
Anti-glare screen	Yes
Screen shape	Curved
Screen curvature rating	2500R
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 800 (WXGA), 1600 x 1200 (UXGA), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1080, 3840 x 2160, 4096 x 2160, 5120 x 2160
Supported video modes	480p, 720p, 1080i, 1080p
Contrast ratio (typical)	1000:1
Maximum refresh rate	60 Hz
Viewing angle. horizontal	178°
Viewing angle. vertical	178°
Display number of colours	1.073 billion colours
Response time (fast)	5 ms
Pixel pitch	0.1815 x 0.1815 mm
Pixel density	140 ppi
Horizontal scan range	27 - 133.286 kHz

Vertical scan range	24 - 86 Hz
Viewable size. horizontal	92.9 cm
Viewable size. vertical	39.2 cm
Viewable size diagonal	100.9 cm
High Dynamic Range (HDR) supported	No
Colour gamut standard	DCI-P3
Colour gamut	98%
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Multimedia	
Number of speakers	2
RMS rated power	18 W
Built-in speaker(s)	Yes
Built-in camera	No
Design	
Market positioning	Graphics design
Product colour	Silver
Front bezel colour	Black
Feet colour	Silver
Ports & interfaces	
Built-in USB hub	Yes
USB upstream port type	USB Type-B
Number of upstream ports	1
Number of USB Type-B upstream ports quantity	1
USB Type-A downstream ports quantity	4
USB Type-C downstream ports quantity	1
USB Power Delivery up to	90 W
DVI port	No
HDMI	Yes
HDMI ports quantity	2
HDMI version	2.0
DisplayPorts quantity	1
DisplayPort version	1.4
Thunderbolt 3 ports quantity	1
Audio input	No

Headphone out	Yes
Headphone outputs	1
Headphone connectivity	3.5 mm
Network	
Wi-Fi	No
Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Cable lock slot	Yes
Height adjustment	Yes
Adjustable height (max)	12 cm
Pivot	No
Swivelling	Yes
Swivel angle range	-30 - 30°
Tilt adjustment	Yes
Tilt angle range	-5 - 21°
Power	
Energy efficiency class (SDR)	G
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	41 kWh
Power consumption (typical)	41.3 W
Power consumption (standby)	0.3 W
Power consumption (max)	240 W
Power consumption (off)	0.3 W
Power consumption (PowerSave)	44.81 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Input current	2.8 A
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions	
Width (with stand)	946.6 mm
Depth (with stand)	248 mm
Height (with stand)	577.3 mm
Weight (with stand)	13.8 kg
Width (without stand)	946.6 mm
Depth (without stand)	59.6 mm
Height (without stand)	419.1 mm
Weight (without stand)	9.5 kg
Bezel width (side)	1.13 cm
Bezel width (top)	1.13 cm
Bezel width (bottom)	1.58 cm
Packaging data	
Package weight	21.6 kg
Carbon footprint	
Total carbon footprint (kg of CO2e)	926
Total carbon emissions, standard deviation (kg of CO2e)	149
Carbon emissions, manufacturing (kg of CO2e)	430.6
Carbon emissions, logistics (kg of CO2e)	112
Carbon emissions, energy usage (kg of CO2e)	377
Carbon emissions, end-of-life (kg of CO2e)	6.23
PAIA version	1.2.13, 2021
Other features	
RJ-45 ports quantity	1
Logistics data	
Harmonized System (HS) code	85285210