

LEVEL ONE

Switch 24x GE GTL-2661 2x10GSFP+19"

SKU: 25012885 · EAN: 4015867203057

SPECIFIKAT TEKNIKE**79 specifikat e produktit**

ATRIBUTI	VLERA
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
Traffic classification	Yes
System event log	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
SFP+ module slots quantity	2
Console port	RJ-45
Network	
Networking standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	Yes
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Rate limiting	Yes
Spanning tree protocol	Yes
Cable length detection	Yes
VLAN support	Yes
Virtual LAN features	Tagged VLAN, MAC address-based VLAN, Port-based VLAN
Data transmission	
Switching capacity	88 Gbit/s

Forwarding rate	65.5 Mpps
MAC address table	16000 entries
Store-and-forward	Yes
Number of queues	8
Static route	Yes
Jumbo frames support	Yes
Jumbo frames	10000
Packet buffer memory	12 MB
Security	
DHCP features	DHCP snooping, DHCP relay, DHCPv6 snooping, DHCP client
Access Control List (ACL)	Yes
Static port security	Yes
SSH/SSL support	Yes
BPDU filtering/protection	Yes
Password protection	Yes
DoS attack prevention	Yes
Protocols	
Management protocols	MLD, Telnet, SNMP V1, V2c & V3, RMON, Web Browser, TFTP
Supported network protocols	IPv4/IPv6
Design	
Rack mounting	Yes
Product colour	Black
Reset button	Yes
LED indicators	Activity, Link, Power
Safety	UL
Performance	
Internal memory	32 MB
Firmware upgradeable	Yes
Telnet	Yes
Fanless	Yes
Mean time between failures (MTBF)	636219 h
Power	
Power source	AC
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz

Power consumption (typical)	20 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Operating relative humidity (H-H)	10 - 90%
Heat dissipation	68.242 BTU/h
Weight & dimensions	
Width	220 mm
Depth	440 mm
Height	44 mm
Weight	2.29 kg
Packaging content	
Cables included	AC, LAN (RJ-45)
Quick start guide	Yes
Rack mount kit	Yes
Packaging data	
Package type	Box
Resource CD	Yes
Package width	405 mm
Package depth	580 mm
Package height	80 mm
Package weight	3.02 kg
Certificates	
Certification	CE class A, FCC, VCCI, BSMI
Logistics data	
Country of origin	China
Master (outer) case width	340 mm
Master (outer) case length	600 mm
Master (outer) case height	435 mm
Harmonized System (HS) code	85176990
Master (outer) case gross weight	11 kg
Products per master (outer) case	4 pc(s)